



电气性能/Electrical

参考标准/Standard:
 额定电压/Rated voltage:
 额定电流/Rated Current:
 接触电阻/Contact resistance:
 绝缘电阻/Insulation resistance:
 使用线径/Wire range:
 耐电压/Wirth standing voltage:

UL IEC
 300V 250V
 8A 7A
 20MΩ
 500MΩ/DC500V
 0.5~1.5mm²/28~18
 1.8KV

机械性能/Mechanical

扭矩/Torque:
 剥线长度/Strip Length:
 温度范围/Temp Range:
 尺寸/Dimensions :

7-8
 -40~+105

间距/Pitch:
 极数/Poles:

3.81/3.5mm
 2P-24P

材质和电镀/Material

器件/Housing:
 螺丝/Screws:
 焊脚/Pin header:
 方块/Cage:
 弹片/Clamp1:
 夹子/Clamp2:

PA66,UL94V-0
 镀Cr3+钝化彩锌
 磷青铜
 黄铜,镀锌

—		new		2015/5/3	A		
ECN BO.		DESCRIPTION.		DATE.	REV.		
DESIGNED	CHECKED	APPROVAL	DRAWING NUMBER	SCALT: 1/2		SCALE: 3:1	
Mikey	Tom	Jerry	PART NAME	HY-3.81-03P	UNLESS OTHERWISE SPECIFIED,TOLERANCE:	X	±0.25
			MODEL NAME	HY-3.81-03P		X.x	±0.20
			3RD ANGLE PROJ	HANYONES TECH CO.,LTD		X.xx	±0.15
					ANGULAR	±3'	FILE. NO.