


线路板开孔尺寸
P.C.B LAYOUT



按点示意图
SCHEMATIC

SPECIFICATION

规格

- 1. Rating: DC 30V, 2A
额定值: 直流30V, 2A
- 2. Contact resistance: $\leq 0.02\Omega$
接触电阻: $\leq 0.02\Omega$
- 3. Insulation resistance: 100m Ω
绝缘电阻: 100m Ω
- 4. Withstand voltage: 250V/min
耐压: 250V/min
- 5. Insertion and extraction force: 3-15N
插拔力: 3-15N
- 6. life: 5, 000 cycles
寿命: 5, 000次循环

4	Terminal	1	H62	Tin
3	Terminal	1	H62	Tin
2	Contact	1	Phospor copper	Tin
1	Base	1	PPA	Black
LTR	PART NAME	1	MATERIAL	PLATED

广东星坤科技股份有限公司

生教 日期

文件工程章

ANGLAR	$\pm 5^\circ$
$L \leq 4$	± 0.2
$4 < L \leq 16$	± 0.3
$16 < L \leq 63$	± 0.4
$L > 63$	± 0.5
REVISIONS	UNSPECIFIED TOLERANCES



DSND	SCALE: N/A	MODEL TYPE: DC POWER JACK
DWN	VIEW:	PART NO.: DC-038
CHKD	UNIT: mm/in	DWG NO.: X-DC-038
APPD	SIZE: A4	WEIGHT SHEET REVISION
XKB INDUSTRIAL PRECISION CO., LIMITED		1/1 A0