


P.C.B LAND PATTERN



CIRCUIT DIAGRAM

SPECIFICATIONS

Rating	50mA 12V DC
Insulation Resistance	50M Ω Min.
Dielectric Withstanding Voltage	AC 250 V(50~60Hz)1min
Contact Resistance	100m Ω Max.
Operating Force	160 \pm 50gf
Operating Life(cycles)	100,000

NO	NAME	MATERIAL	QTY	FINISHING
7				
6				
5	THERMINAL	PHOSPHOR BRONZE	3	Ag plated
4	CONTACT	SUS	2	Ag plated
3	COVER	PHOSPHOR BRONZE	1	Ag plated
2	BASE	LCP	1	Black
1	STEM	PPA	1	White

单位 UNIT	mm	一般公差 GENERAL TOLERANCE		东莞市台溢电子有限公司			
制图 DRAW	杜娟	.X \pm 0.5	ANGLES				
设计 DESIGN	李海斌	.XX \pm 0.2	X \pm 5	公司网址: Company website	http://www.tydz888.com		
审核 CHECKED	谭兵	.XXX \pm 0.1	.X. \pm 2	名称 TITLE	轻触开关		
校准化 STANDARD	彭勇	重量 WT.		型号 MODEL	T1-A0412	日期 DATE	2018/05/12
批准 APPROVE	肖辉华	表面积 SA.		角法 PROJ.		比例 SCALE	1:1
					版本 REV.	AO	