



| | | | | |
|---|-------|-------|-------|-------|
| | 三型 | 四型 | 六型 | 九型 |
| A | 7.62 | 10.16 | 15.24 | 22.86 |
| B | 4.14 | 6.68 | 11.76 | 19.38 |
| C | 10.12 | 12.66 | 17.74 | 25.36 |

ELECTRICAL:
 CURRENT RATING: 300mps/CONTACT MAX.
 CONTACT RESISTANCE: 20mΩ/CONTACT MAX.
 INSULATION RESISTANCE: 1000MΩ AT V=100V MIN.
 OPERATING VOLTAGE: 60V AC/DC

MECHANICAL:
 AVERAGE INSERTION FORCE WITH STEEL PIN OF Ø0.43mm: 250g MAX.
 AVERAGE WITH TIRAL FORCE WITH STEEL PIN OF Ø0.43mm: 25G MIN.
 MECHANICAL LIFE CYCLE: 200 CYCLE MIN.
 OPERATING TEMPERATURES: GOLD PLATED: -55°C TO +125°C
 TIN PLATED: -40°C TO +105°C
 SOLDERING TEMPERATURE: PBT, +240°C, 10S MAX.

MATERIAL:
 PIN: BRASS, MACHINED
 CLIP: BERYLLIUM COPPER OR PHOSPHOR BRONZE
 INSULATOR BODY: BLACK PBT OR OTHER (UL94V-0)

| CODE | PIN PLATED | CLIP PLATED |
|------|------------|-------------|
| 1001 | TIN 200μ | GOLD FLASH |
| 1003 | TIN 200μ | GOLD 10μ |
| 1005 | TIN 200μ | GOLD 30μ |
| 1007 | TIN 200μ | TIN 200μ |
| 1301 | GOLD FLASH | GOLD FLASH |
| 1303 | GOLD FLASH | GOLD 10μ |
| 1305 | GOLD FLASH | GOLD 30μ |
| 1307 | GOLD FLASH | TIN 200μ |

| REV. | DESCRIPTION | DATE | DRAWN |
|------|----------------|----------|-------|
| B | PART NO MODIFY | 3/11/16 | 楊海文 |
| A1 | PART NO MODIFY | 8/17/11 | 廖小濤 |
| A | NEW RELEASED | 10/28/09 | 陳惠長 |

正達精密工業(廣州)有限公司
 2016/3/18
 内部资料请勿复印