



MATERIAL:
 Ⓜ HOUSING: THERMOPLASTIC, GLASS FIBER FILLED. UL 94V-0 RATED.
 Ⓜ SPACER: THERMOPLASTIC, GLASS FIBER FILLED. UL 94V-0 RATED.
 Ⓜ CONTACT: C5191R-H (t=0.30mm).
 Ⓜ FRONT SHIELD: SPCC (t=0.40mm).

FINISH:
 CONTACT: UNDER PLATED 50u" MIN. NICKEL ALL OVER 100u" MIN. MATTE TIN IN SOLDERING AREA GOLD PLATED IN CONTACT AREA.
 FRONT SHIELD: NICKEL PLATED WITH 100u" THICK.

HOUSING COLOR	PACKAGE
1:BLACK	0:TRAY
CONTACT GOLD PLATED	SHELL PLATING
A:G/F+MATTE TIN	N:NICKEL

PART NO. DESCRIPTION:
 DOR02-15 - X
 Ⓜ MARK
 0:NON MARK
 5: +D/C
 X: XKB+D/C

					ANGLAR	±5°	DSND		DATE		SCALE: N/A	MODEL TYPE:		
					L ≤ 4	±0.2	DWN		DATE		VIEW:	DB CONNECTOR		
					4 < L ≤ 16	±0.3	CHKD		DATE		UNIT: mm/in	PART NO.:		
					16 < L ≤ 63	±0.4	APPD		DATE		SIZE: A4	DWG NO.:		
					L > 63	±0.5						DOR02-15-X		
MARK					UNSPECIFIED TOLERANCES		XKB INDUSTRIAL PRECISION CO., LIMITED					WEIGHT	SHEET	REVISION
REVISIONS												1.0g	1/1	A0
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn														