



PARTS LIST

ITEMS	DESCRIPTION	REF. DATA	REQ.
1	GRID	COPPER NICKEL ALLOY (T11)	3
2	GAGE LEAD	POLYURETHANE WIRE $\phi 0.14 \times 300$ mm	6
3	BASE	EPOXY	3
4	COVER	POLYESTER	1
5	LEAD WIRE	7/0.12 2C DIA 1mm	3

SPECIFICATIONS

RESISTANCE : $120.0 \Omega \pm 1.0 \Omega$
 GAGE LENGTH : 1mm
 GAGE FACTOR : 1.9~2.1
 TEMPERATURE RANGE : -50°C to 70°C

LEAD JUNCTION : SOLDER



ミネベア株式会社 MINEBEA CO.,LTD. 計測機器事業部			単位 UNIT mm 尺度 SCALE FREE		材質 MATERIAL -	作成日 DATE 2005.12.22
APPROVED CHECKED DRAWN			一般公差 TOL		表面粗さ SURF.ROUGH. -	品名 DESCRIPTION FR-1A12L30W05MS
符号 MARK	日付 DATE	ECN NO.	担当 ENGINEER D. Inomori	承認 APPROVED E. MISAIZU	熱処理 HEAT TREAT. -	品番 PART NO. (MODEL NO.) -
			承認 APPROVED M. HIRAMOTO	公差 TOL	表面処理 FINISH -	図番 DRAWING NO. G900245-1
				寸法 L 公差 $L \leq 4$ ± 0.1 $4 < L \leq 16$ ± 0.2 $16 < L \leq 63$ ± 0.3 $63 < L \leq 250$ ± 0.5 $250 < L \leq 1000$ ± 0.8 角度 DEG ± 0.5	表面処理 FINISH -	葉番 SHEET /
					改訂 REV. -	