

Fast Acting SMD 125VAC/DC Fuse

2410FA Series

Descriptions

2410FA Series SMD fuse for the small size and good electrical performance, reliability and quality.



Electrical Characteristics

Current Rating	% of Ampere Rating	Opening Time
500mA-15A	100%	4 hours Min
500mA-15A	200%	5 sec Max



Features

- Designed to UL 248-14
- Small size
- Compatible with reflow and wave soldering RoHS compliant and Halogen Free
- One time positive disconnect

Application

- Notebook PC
- Backlight inverter
- Power supply
- Storage system
- Telecom system
- Battery charging circuit protection
- Industrial equipment

Specification


Product Code	Current Rating	Voltage Rating	Interrupting Rating	Resistance (ohms) Typ.	Typical Melting I ² t (A ² Sec)	Typical Voltage Drop (mV)
2410FA-R500	0.5A	125VAC 125VDC	125VAC@50A 125VDC@50A	0.28100	0.48	185
2410FA-R800	0.8A			0.13700	1.70	150
2410FA-1A	1.0A			0.10500	2.70	140
2410FA-1.5A	1.5A			0.06200	4.90	125
2410FA-2A	2.0A			0.02700	1.50	96
2410FA-2.5A	2.5A			0.01820	5.50	60
2410FA-3A	3.0A			0.01780	3.10	86
2410FA-4A	4.0A			0.01290	5.20	85
2410FA-5A	5.0A			0.01020	8.50	81
2410FA-6.3A	6.3A			0.00770	15.0	80
2410FA-7A	7.0A			0.00720	19.5	80
2410FA-8A	8.0A			0.00630	24.0	78
2410FA-10A	10A			0.00510	38.0	77
2410FA-12A	12A			0.00395	57.0	76
2410FA-15A	15A			0.00315	105.0	75

- AC Interrupting Rating (measured at designated voltage, 100% power factor); DC Interrupting Rating (measured at designated voltage, time constant of less than 50 microseconds, battery source)
- DC Cold Resistance are measured at <10% of rated current in the ambient temperature of 25°C
- Typical Pre-arcing I²t are measured at 10In Current

Fast Acting SMD 125VAC/DC Fuses

2410FA Series


Dimension




Packaging

- Quantity: 1,000pcs
- 12mm wide tape on 178mm(7 inch) diameter reel -specification EIA Standard 481.


1A-10A Pad layout



12A-15A Pad layout



Soldering Parameters




Wave Soldering: 260°C , 10 seconds max.
 Infrared Reflow: 260°C , 30 seconds max.

IR Reflow Profile

Preheat Heat	
Temperature min (T_{Smin})	150°C
Temperature max (T_{Smax})	200°C
Time (T_{Smin} to T_{Smax}) (t_{S})	60 - 120 seconds
Average ramp-up rate (T_{Smax} to T_{P})	
	$3^{\circ}\text{C/second max.}$
Liquidous temperature (T_{L})	
Time at liquidous (t_{L})	60 - 150 seconds
Peak temperature (T_{P})	
	$260 \pm 0/-5^{\circ}\text{C}$
Time within 5°C of actual peak Temperature (t_{P})	
	10 - 30 seconds
Average ramp-down rate (T_{P} to T_{Smax})	
	$6^{\circ}\text{C/second max.}$
Time 25°C to peak temperature	
	8 minutes max.

Temperature Derating Curve




- Normal Operating Temperature: $25^{\circ}\text{C} \pm 2^{\circ}\text{C}$
 - Operating Temperature: -55°C to 125°C with proper correction factor applied.
- Chart of correction factor
 Storage Temperature: -55°C to 125°C

Fast Acting SMD 125VAC/DC Fuses

2410FA Series

Time Current Curves



Time Current Curves

