

## **TUNER AFC DIODE**

The 1S2638 is a variable capacitor diode intended for AFC applications, VHF TV applications, FM receivers. Air craft communications gear, and other receivers in the 1 MHz to 500 MHz.

Standard package is DO-35 case, DO-34 case is available upon request.





Dimensions in mm

Glass Case DO-34 Dimensions in mm

Absolute Maximum Ratings ( $T_a = 25 \, ^{\circ}$ C)

1.000 1.000			
Parameter	Symbol	Value	Unit
Breakdown Voltage	BV	10	V
Forward Current	I <sub>F</sub>	250	mA
Power Dissipation	P <sub>D</sub>	350	mW
Operating Temperature Range	T <sub>opr</sub>	- 65 to + 175	°C
Storage Temperature Range	T <sub>stg</sub>	- 65 to + 200	°C

## Characteristics at T<sub>a</sub> = 25 °C

Parameter	Symbol	Min.	Max.	Unit
Reverse Current at V <sub>R</sub> = 10 V	I <sub>R</sub>	-	5	μΑ
Nominal Capacitance at V <sub>R</sub> = 4 V, f = 1 MHz	С	5	20	pF
at V <sub>R</sub> = 4 V, f = 100 MHz	Q	50	-	-









