



NOTES:

ELECTRICAL:

1. VOLTAGE RATING
2. CURRENT RATING
3. CONTACT RESISTANCE
4. INSULATION RESISTANCE
5. DIELECTRIC STRENGTH

MECHANICAL:

1. HOUSING&INSERT MATERIAL
2. CONTACT MATERIAL
3. PLATING
4. OPERATING LIFE
5. MATING/UNMATING FORCE
6. RETENTION STRENGTH

- ! 125 VAC RMS.
- ! 1.5 AMP.
- ! 20 MILLIOMHS MAX.
- ! 1000 MEGOHMS MIN @ 500 VDC
- ! 1000 V AC OR 1500V DC RMS @ 0.5mA 50 Hz / 60 Hz 1 Minute

- ! (SEE TABLE) UL 94V-0.
- ! PHOSPHOR BRONZE Ø0.46mm.
- ! GOLD PLATING OVER NICKEL.
- ! 750 CYCLES MIN.
- ! 30N MAX.
- ! 50N FOR 60S±5S.

ENVIRONMENTAL:

1. STORAGE : -40°C TD +85°C RELATIVE HUMIDITY<80%.
 2. OPERATION : -40°C TD +85°C.
- MATES WITH MODULAR PLUG CONFIRMING TO FCC PART 68, SUBPART F.

- 电气特性:**
- 1.额定电压: 125 VAC RMS
 - 2.额定电流: 1.5 AMP
 - 3.接触电阻: 20mΩ MAX
 - 4.绝缘电阻: 1000MΩMIN @500 VDC
 - 5.耐压强度: 1000 V AC 或 1500V DC RMS @ 0.5mA 50 Hz 或 60 Hz 一分钟

结构特性:

1. 金属材料: (见屏飞表接) 0.94V-0
 2. 零件材质: 磷青铜, Ø0.46mm
 3. 零件电镀: 表面镀金(见零件表接), 镀层: 4.可溶性: 至少750次插拔.
 5. 插入/拔出力: 30N Max
 6. 配合精度: 50μ 60μ ±5μ.
- 环境特性:**
1. 储存温度: -40°C ~ +85°C
 2. 工作温度: -40°C ~ +85°C
- 相对湿度 <80%

TOLERANCE TABLE

.0	±0.30
.00	±0.20
.000	±0.05

APPROVED:	DATE:	TITLE:	CLIENT P/N	UNIT	SCALE	free	REV.	A	KYD0
CHECKED:	DATE:	RJ11-6P/6C 全塑 弯插 (AJ007) 无标	C2902899	mm	SCALE	free	REV.	A	KYD0
DRAWN:	DATE:	深圳市灿科盟实业有限公司	R-RJ11R06P-A000	mm	SCALE	free	REV.	A	KYD0
LXF	2011-01-13	CHANKUANGMENT INDUSTRYCO., LTD		mm	SCALE	free	REV.	A	KYD0