



Dimension:

POLES	PART No.	Dim. A	Dim. B	Dim. C	Dim. D
6	101-2-6P	4.00	7.10	11.20	5.00
8	101-2-8P	6.00	9.10	13.20	7.00
10	101-2-10P	8.00	11.10	15.20	9.00
12	101-2-12P	10.00	13.10	17.20	11.00
14	101-2-14P	12.00	15.10	19.20	13.00
16	101-2-16P	14.00	17.10	21.20	15.00
18	101-2-18P	16.00	19.10	23.20	17.00
20	101-2-20P	18.00	21.10	25.20	19.00
22	101-2-22P	20.00	23.10	27.20	21.00
24	101-2-24P	22.00	25.10	29.20	23.00
26	101-2-26P	24.00	27.10	31.20	25.00
28	101-2-28P	26.00	29.10	33.20	27.00
30	101-2-30P	28.00	31.10	35.20	29.00
32	101-2-32P	30.00	33.10	37.20	31.00
34	101-2-34P	32.00	35.10	39.20	33.00
36	101-2-36P	34.00	37.10	41.20	35.00
40	101-2-40P	38.00	41.10	45.20	39.00
44	101-2-44P	42.00	45.10	49.20	43.00
50	101-2-50P	48.00	51.10	55.20	49.00
60	101-2-60P	58.00	61.10	65.20	59.00
64	101-2-64P	62.00	65.10	69.20	63.00
68	101-2-68P	66.00	69.10	73.20	67.00

Material

Insulator : P.B.T+30% Glass Fiber (UL94V-0)

Contact : Phosphor Bronze or Brass

Contact Plated : Gold over Nickel or Tin

Specification

Current Rating : 1A

Insulation Resistance : 1000MΩ Min. at 500V DC

Dielectric Withstanding Voltage: 500V AC for 1 Minute

Operation Temperature : -55℃ ~ +105℃

Contact Resistance : 15mΩ Max

TOLERANCE TABLE

.0	±0.20
.00	±0.10
.000	±0.05

APPROVED:	DATE:	 深圳市灿科盟实业有限公司 CHANKEMENG INDUSTRYCO., LTD	TITLE:				
CHECKED:	DATE:		101-2-XP 二件式 有凸				
DRAWN:	DATE:	CLIENT P/N	/				
LXF	2008-04-07	UNIT	mm	SCALE	free	REV.	A
		FILE NO.	CKM-101-00002				