



Product features

- Voltage: < 12V
- Current: < 20mA
- Conduction time: 2ms
- Closed circuit resistance: < 10m ohm
- Open circuit resistance: > 10m ohm
- High temperature resistance: 120 degrees
- Terminal tension: 500gf / min
- Humidity: 25~95%RH
- Operating life: 100000 times

Product features

- 产品特点
- 1.460D is double ball type single direction tilt induction trigger switch.
1.460D为双球型单向倾斜感应触发开关。
 2. When the electric end of the product guide (foot less) is tilted and the tilt Angle is greater than 10 degrees, the product is in the open, (OFF) state. When the horizontal state of the product is tilted and the trigger end (gold-plated pin end) is lower than the horizontal and the tilt Angle is greater than 10 degrees, the product is in the closed, (ON) state.
2.当产品导轨（无脚）的电气端倾斜且倾斜角度大于10度时，产品处于打开（关闭）状态。当产品水平状态倾斜，触发端（镀金销端）低于水平且倾斜角度大于10度时，产品处于闭合（开）状态。
 3. When placed horizontally, shaking can be easily triggered, and when there is no foot down, shaking is not easy to trigger.
3.水平放置时，很容易触发震动，没有脚下来时，不容易触发震动。
 4. The products of this specification are completely sealed, waterproof and dustproof.
4.本规范产品全密封、防水、防尘。
 5. Under normal circumstances, the switching life can reach 100,000 times.
5.正常情况下，开关寿命可达10万次。
 6. This product is made of environment-friendly metal material with stable performance.
6.本产品采用环保型金属材料，性能稳定。

⑦	Heat shrinkable tube	1	Pet heat shrinkable tube	
⑥	Rubber stopper	1	PLC	
⑤	BALL	1	Brass	Nickel
④	BALL	1	Brass	Silver
③	PIN B	1	Brass	Gold
②	PIN A	1	Brass	TIN
①	Copper pipe	1	Brass	Nickel
ITEM	PAPT NAMF	QTY	MATERIAL	FINISHING

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE
	A		B	



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT	MM	PROJECTED		PRODUCT NAME:
DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TPSW-460
DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
ROCPCU TECHNOLOGY CO.,LTD				
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				
D	E	F	G	