


NOTES:

1. Rating: 12VDC 50mA
1. 额定值: 12VDC 50mA
2. Dielectric Strength: 250V AC
2. 耐电压: 250V AC
3. Contact Resistance: $\leq 100\text{m}\Omega$ Max
3. 接触电阻: $\leq 100\text{m}\Omega$
4. Insulation Resistance: $\geq 100\text{M}\Omega$
4. 绝缘电阻: $\geq 100\text{M}\Omega$


5. Operating Force: $260 \pm 50\text{gf}$
5. 操作力: $260 \pm 50\text{gf}$
6. Life: 100,000 times
6. 寿命: 100,000 times
7. Travel: $0.25 \pm 0.1\text{mm}$
7. 行程: $0.25 + 0.1\text{mm}$
8. Operating Temperature: -20 to $+70^\circ\text{C}$
8. 使用温度: -20 to $+70^\circ\text{C}$

7	Key cap 按键帽	PET	1	
6	Key cap 按键帽	ABS	1	White 白色
5	LED		1	Red 红灯
4	Button 按钮	POM	1	
3	Shrapnel 弹片	SUS	1	
2	Pedestal 基座	PA66	1	
1	Terminal 端子	Brass	4	Ag plating 镀银
NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注

PCB LAYOUT



CIRCUIT



COMMON TOLERANCE

X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT

MM

PROJECTED



PRODUCT NAME:

DRAWN BY

FUYUAN

CHECKED BY

COCO

MODEL NO: TPB01-104L1W

DATE

2019

APPROVAL B

ALEN

Https: www.rocpcu.tw

ROCPCU TECHNOLOGY CO.,LTD

Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission