




CMOS/ 1.8V to 3.3V/ 2.0×1.6mm



RoHS Compliant

Features

- Ultra Miniature ceramic package
2.0 (L) × 1.6 (W) × 0.55 (H) mm (Typ.)
- Highly reliable with seam welding
- CMOS output
- Supply voltage V_{cc}=1.8V/ 2.5V/ 3.3V
- Wide operating voltage range 1.6 to 3.63V
- Low current consumption

Table 1

Freq. Tol.	Operating Temperature Range (°C)	Note
Code × 10 ⁻⁶		
0 ± 50	-10 to +70	Standard specifications
S ± 30		Please contact us for available frequencies.
U ± 25		
F ±100		
G ± 50	-40 to +85	
6 ± 50	-40 to +105	

How to Order

KC2016B 40.0000 C 1 □ E 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (1.8V, 2.5V, 3.3V Compatible)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 2000 pcs./ reel)


Specifications

Item	Symbol	Conditions	Min.	Max.	Unit
Output Frequency Range	f _o		1.5	50	MHz
Frequency Tolerance	f _{tol}	Initial tolerance, Operating temperature range, Rated power supply voltage change, Aging (1 year @25°C), Shock and vibration	Temp.: -40 to +85°C	-100	+100
			Temp.: -10 to +70°C/ -40 to +85°C/ -40 to +105°C	-50	+50
			Temp.: -10 to +70°C	-30	+30
			Temp.: -10 to +70°C	-25	+25
Storage Temperature Range	T _{stg}		-55	+125	°C
Operating Temperature Range	T _{use}	Standard Specifications	-10	+70	°C
		Extend (Option)	-40	+85	
Max. Supply Voltage	—		-0.6	+6.0	V
Supply Voltage	V _{cc}		+1.6	+3.63	V
Current Consumption (Maximum Loaded/ 1.6≤V _{cc} ≤2.0V)	I _{cc}	1.5≤f _o ≤24MHz	—	2.5	mA
		24<f _o ≤40MHz	—	3.5	
		40<f _o ≤50MHz	—	4.5	
Current Consumption (Maximum Loaded/ 2.0<V _{cc} ≤2.8V)	I _{cc}	1.5≤f _o ≤24MHz	—	3.0	
		24<f _o ≤40MHz	—	4.5	
		40<f _o ≤50MHz	—	5.0	
Current Consumption (Maximum Loaded/ 2.8<V _{cc} ≤3.63V)	I _{cc}	1.5≤f _o ≤24MHz	—	3.5	
		24<f _o ≤40MHz	—	5.0	
		40<f _o ≤50MHz	—	6.0	
Stand-by Current	I _{std}		—	10	μA
Symmetry	SYM	@50% V _{cc}	45	55	%
Rise/ Fall Time (10% V _{cc} to 90% V _{cc} Maximum Loaded)	Tr/ Tf	1.6≤V _{cc} ≤2.0V	—	6.5	ns
		2.0<V _{cc} ≤2.8V	—	5.0	
		2.8<V _{cc} ≤3.63V	—	4.5	
Low Level Output Voltage	V _{OL}	I _{OL} =4mA	—	10% V _{cc}	V
High Level Output Voltage	V _{OH}	I _{OH} =-4mA	90% V _{cc}	—	V
CMOS Load	L _{CMOS}	CMOS Output	—	15	pF
Input Voltage Range	V _{IN}		0	V _{cc}	V
Low Level Input Voltage	V _{IL}		—	30% V _{cc}	V
High Level Input Voltage	V _{IH}		70% V _{cc}	—	V
Disable Time	t _{dis}		—	100	ns
Enable Time	t _{ena}		—	5	ms
Start-up Time	t _{str}	@Minimum operating voltage to be 0 sec.	—	10	ms
1 Sigma Jitter	J _{Sigma}	Measured with Wavcrest SIA-3000	—	8	ps
Peak to Peak Jitter	J _{PK-PK}		—	80	ps

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Dimensions

(Unit: mm)



Recommended Land Pattern

(Unit: mm)

