



Surface Mount Ultrafast Recovery Rectifier

Reverse Voltage – 50~1000 V

Forward Current – 5 A

FEATURES


- For surface mounted applications
- Low profile package
- Glass Passivated Chip Junction
- Superfast reverse recovery time
- Lead free in comply with EU RoHS 2011/65/EU directives

MECHANICAL DATA

- Case: SMC
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 217mg / 0.0077oz

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode



Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20 %.

Parameter	Symbols	US5AC	US5BC	US5DC	US5GC	US5JC	US5KC	US5MC	Units			
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V			
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	V			
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V			
Maximum Average Forward Rectified Current at $T_c = 100$ °C	$I_{F(AV)}$	5							A			
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load	I_{FSM}	120							A			
Maximum Instantaneous Forward Voltage at 5 A	V_F	1.0		1.3	1.65			V				
Maximum DC Reverse Current $T_a = 25$ °C at Rated DC Blocking Voltage $T_a = 125$ °C	I_R	5 100							µA			
Typical Junction Capacitance at $V_R=4V$, $f=1MHz$	C_j	50							pF			
Maximum Reverse Recovery Time ⁽¹⁾	t_{rr}	50			75			ns				
Typical Thermal Resistance ⁽²⁾	$R_{\theta JA}$	35							°C/W			
Operating and Storage Temperature Range	T_j , T_{stg}	-55 ~ +150							°C			

(1) Measured with $I_F = 0.5$ A, $I_R = 1$ A, $I_{rr} = 0.25$ A.

(2) P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.



Fig.1 Reverse Recovery Time Characteristic And Test Circuit Diagram





Fig.2 Maximum Average Forward Current Rating




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Forward Characteristics




Fig.5 Typical Junction Capacitance





Fig.6 Maximum Non-Repetitive Peak Forward Surge Current






PACKAGE OUTLINE

Plastic surface mounted package; 2 leads


SMC



SMC mechanical data

UNIT		A	E	D	E ₁	A ₁	C	L	b
mm	max	2.62	7.0	6.2	8.0	0.21	0.31	1.6	3.25
	min	2.00	6.5	5.6	7.6	0.05	0.15	0.9	2.75
mil	max	103	276	244	315	8.3	12	63	128
	min	79	256	220	299	2.0	5.9	35	108

The recommended mounting pad size



Marking

Type number	Marking code
US5AC	US5A
US5BC	US5B
US5DC	US5D
US5GC	US5G
US5JC	US5J
US5KC	US5K
US5MC	US5M