



常态：1-3导通 4-6导通  
按下：2-3导通 4-5导通

Technical parameter

- 技术参数  
1. Rated current: 100mA 30V DC  
1. 额定电流：100mA 30V DC  
2. Contact resistance:  $\leq 10 \Omega$   
2. 接触电阻： $\leq 10 \Omega$   
3. Operating force: 260gf  $\pm$  50gf  
3. 操作力：260gf  $\pm$  50gf  
4. Maximum stroke: 3.0  $\pm$  0.2mm

4. 最大行程：3.0  $\pm$  0.2mm  
5. Insulation resistance:  $\geq 100M \Omega$   
5. 绝缘电阻： $\geq 100M \Omega$   
6. Electric strength: AC250V 50Hz 1min  
6. 抗电强度：AC250V 50Hz 1min  
7. Service life: 10000 times  
7. 寿命：10000次  
8. Switch similar: Self locking  
8. 开关类似：自锁

7	crochet hook 钩针	SUS 不锈钢丝	1	Natural color 本色
6	Spring 弹簧	SUS 不锈钢丝	1	Natural color 本色
5	reed 簧片	Composite silver 复合银	1	Natural color 本色
4	Upper cover 上盖	PPA	1	black 黑色
3	handle 按柄	PA66 尼龙66	1	black 黑色
2	terminal 端子	Brass 黄铜	1	Natural color/silver 本色/镀银
1	Pedestal 基座	PPA	1	black 黑色
ITEM	Name	Materials	NUM	COLOR

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE

X.XX	$\pm 0.10$
X.X	$\pm 0.15$
X	$\pm 0.25$
ANGULAR	—

UNIT

MM

PROJECTED



PRODUCT NAME:

DRAWN BY

FUYUAN

CHECKED BY

COCO

MODEL NO: BTSA-L-P-15

DATE

2019

APPROVAL B

ALEN

Https: www.rocpcu.tw

**ROCPCU TECHNOLOGY CO.,LTD**

Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basis of manufacture or sale of apparatus without permission