

Valve connectors - SAC-3P-M12MS/A-1L-S



1505258

<https://www.phoenixcontact.com/us/products/1505258>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Valve connector type A, PE bridged, 18 mm contact spacing, vertical connector M12



Commercial Data

Item number	1505258
Packing unit	1 pc
Minimum order quantity	5 pc
Note	Made to Order (non-returnable)
Sales Key	00
Product Key	BF1GDA
Catalog Page	Page 172 (PC-2011)
GTIN	4017918857042
Weight per Piece (including packing)	38.62 g
Weight per Piece (excluding packing)	35.68 g
Customs tariff number	85366990
Country of origin	CZ

Valve connectors - SAC-3P-M12MS/A-1L-S



1505258

<https://www.phoenixcontact.com/us/products/1505258>

Technical Data

Product properties

Product type	Valve connector adapter
Number of positions	3
No. of cable outlets	1
Coding	A - standard

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Color	black
Flammability rating according to UL 94	V0
Sealing material	TPU
Material housing valve plug	PBT
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Contact material	CuSn
Valve plug contact insert material	PBT
Contact surface material	Ag
Cable gland material	Zinc die-cast, nickel-plated

Electrical properties

Contact resistance	≤ 15 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U_N	24 V AC
	24 V DC
Nominal current I_N	4 A
Protective circuit	Z diode

LED signaling

Status display	Yellow LED
Status display present	yes

Connection data

Connection method	M12 connector
Tightening torque	0.4 Nm (M12 connector)
	0.6 Nm (Valve connector)

Connector

Valve connectors - SAC-3P-M12MS/A-1L-S



1505258

<https://www.phoenixcontact.com/us/products/1505258>

Insertion/withdrawal cycles	≥ 100
-----------------------------	-------

Connection 1

Head design	Plug
Head cable outlet	straight
Head thread type	M12
Coding	A

Connection 2

Head design	Valve connector
Head thread type	A
Status indicator head	1 LED

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C ... 85 °C (valve plug)

Standards and regulations

M12

Standards/specifications	IEC 61076-2-101
--------------------------	-----------------

Valve connector

Standards/specifications	EN 175301-803
--------------------------	---------------


Valve connectors - SAC-3P-M12MS/A-1L-S

1505258

<https://www.phoenixcontact.com/us/products/1505258>


Drawings

Schematic diagram



Valve connector pin assignment, type A

Dimensional drawing



Valve connector, type A with vertical M12 plug


Valve connectors - SAC-3P-M12MS/A-1L-S

1505258

<https://www.phoenixcontact.com/us/products/1505258>




Schematic diagram



Pin assignment M12 plug, 3-pos., A-coded, view male side

Circuit diagram



Valve connectors - SAC-3P-M12MS/A-1L-S



1505258

<https://www.phoenixcontact.com/us/products/1505258>

Classifications

ECLASS

ECLASS-11.0	27440105
-------------	----------

Valve connectors - SAC-3P-M12MS/A-1L-S



1505258

<https://www.phoenixcontact.com/us/products/1505258>

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50 years For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"
------------	--

Valve connectors - SAC-3P-M12MS/A-1L-S

1505258

<https://www.phoenixcontact.com/us/products/1505258>

Accessories

Sensor/actuator cable

Sensor/actuator cable - SAC-3P-M12MS/3,0-PUR/M12FS 345 - 1402560

<https://www.phoenixcontact.com/us/products/1402560>



Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, coding: A, on Socket straight M12, coding: A, cable length: 3 m, For valve connector

Sensor/actuator cable

Sensor/actuator cable - SAC-3P-M12MS/5,0-PUR/M12FS 345 - 1402561

<https://www.phoenixcontact.com/us/products/1402561>



Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, coding: A, on Socket straight M12, coding: A, cable length: 5 m, For valve connector

Valve connectors - SAC-3P-M12MS/A-1L-S



1505258

<https://www.phoenixcontact.com/us/products/1505258>

Sensor/actuator cable

Sensor/actuator cable - SAC-3P-M12MS/10,0-PUR/M12FS 345 - 1402562

<https://www.phoenixcontact.com/us/products/1402562>



Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, coding: A, on Socket straight M12, coding: A, cable length: 10 m, For valve connector

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com