



Z5-DS

PROJECT INFORMATION

Project Name _____

Catalog No. _____ Date _____

The *Zone5* Daylight Sensor provides the necessary daylight-level information to the *Zone5* Control Module (ZCM). Using a photodiode element, this sensor continuously measures daylight levels and sends the information to the ZCM for daylight harvesting with lighting in the General (GEN) lighting mode. The daylight sensor supports multiple foot-candle ranges which can be used in normal, skylight or atrium lighting applications.

PRODUCT FEATURES

- Daylight sensor for *Zone5* Daylight Harvesting System
- Architecturally attractive design
- Open loop operation
- Foot-candle range: 3-6,000 fc
- Mounts vertically or horizontally
- Color coded, plug-and-play installation
- UL and cUL listed
- Five-Year Warranty
- Low voltage device: 24 Vdc

General Specifications

Electrical	Three jumper-selectable foot-candle ranges: 3-300fc; 30-3,000fc; 60-6,000fc 24VDC Power provided through plenum rated CAT5 plug and play cable (ordered separately)
Construction	Protective hard plastic cover and housing
Dimension	2" diameter x 1.2" height (50.8 diameter x 30.5mm height)
Certifications	UL and cUL listed
Warranty	Five years

Ordering Information

Z5-DS	
MODEL	
Z5-DS	<i>Zone5</i> Daylight Sensor



HUBBELL
Control Solutions