
## **Spec Sheet**

# SMD Power Inductors (NR series S type)

## NRS4018T4R7MDGJ



#### Features

- Item Summary
  4.7uH±20%, 1.7A, 4.0x4.0x1.8mm
- Lifecycle Stage
  - Mass Production
- Standard packaging quantity (minimum)
  Taping Embossed 3500pcs


#### Products characteristics table

Inductance	4.7 uH ± 20 %
Case Size (mm)	4.0x4.0
Rated Current (max)	1.7 A
Saturation Current (max)	2 A
Saturation Current (typ)	2.33 A
Temperature Rise Current (max)	1.7 A
Temperature Rise Current (typ)	1.88 A
DC Resistance (max)	84 mΩ
DC Resistance (typ)	70 mΩ
LQ Measuring Frequency	100 kHz
Self Resonant Frequency (min)	35 MHz
Operating Temp. Range	-25 to +125 ℃ (Including-self-generated heat)
Temperature characteristic (Inductance change)	± 20 %
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (168 subst.)	Yes
Soldering	Reflow

#### External Dimensions

Dimension L	4.0 ±0.2 mm
Dimension W	4.0 ±0.2 mm
Dimension H	Max 1.8 mm
Dimension e	1.1 ±0.2 mm
Dimension f	2.5 ±0.2 mm

## Recommended Land Patterns



2017.01.02

Unit: mm

## SMD Power Inductors (NR series S type)

### NRS4018T4R7MDGJ

Dimension unit : mm unit: inch Length: 4.0 + / - 0.2(0.157 + / - 0.008)Width: 4.0 +/- 0.2 (0.157 + / - 0.008)max. ) Height: 1.8 max. (0.071



Inductance: 4.7 (test freq at 0.1MHz) иΗ DC Resistance: 0.07 / 0.084 ohm (typ/max)

Saturation Current: 2,000 mA (max) 1,700 mA ( max ) Temp. rise Current:

> Saturation current typical: 30% reduction from initial L value. Temp rise Current typical: Temperature will rise by 40 deg C

