

LOS-M

~25° medium beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.

TECHNICAL SPECIFICATIONS:

Dimensions	Ø 21.6 mm
Height	14.3 mm
Fastening	glue, pin
ROHS compliant	yes ⓘ

MATERIAL SPECIFICATIONS:






Component	Type	Material	Colour	Finish
LXP2-M	Single lens	PMMA	clear	
LEILA-HLD-OSL	Holder	PC	white	



ORDERING INFORMATION:

Component	Type	Qty in box	MOQ	MPQ	Box weight (kg)
CP12414_LOS-M	Single lens	1680	336	112	10.0
» Box size: 480 x 280 x 300 mm					

PHOTOMETRIC DATA (MEASURED):

<p>NICHIA</p> <p>LED NF2x757A FWHM / FWTM 25.0° / 42.0° Efficiency 92 % Peak intensity 4.9 cd/m LEDs/each optic 1 Light colour White Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED Duris S5 (2 chip) FWHM / FWTM 24.0° / 43.0° Efficiency 92 % Peak intensity 4.9 cd/m LEDs/each optic 1 Light colour White Required components:</p>	 
<p>OSRAM Opto Semiconductors</p> <p>LED OSLON Square EC FWHM / FWTM 25.0° / 43.0° Efficiency 92 % Peak intensity 4.8 cd/m LEDs/each optic 1 Light colour White Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED OSLON SSL 150 FWHM / FWTM 22.0° / 39.0° Efficiency 87 % Peak intensity 3.9 cd/m LEDs/each optic 1 Light colour White Required components:</p>	

PHOTOMETRIC DATA (MEASURED):


OSRAM
Opto Semiconductors

LED	OSLON SSL 80
FWHM / FWTM	23.0° / 40.0°
Efficiency	93 %
Peak intensity	3.8 cd/m
LEDs/each optic	1
Light colour	White
Required components:	


PHOTOMETRIC DATA (SIMULATED):




LED XQ-E HD
FWHM / FWTM 28.0° / 44.0°
Efficiency 95 %
Peak intensity 4.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON C
FWHM / FWTM 26.0° / 44.0°
Efficiency 94 %
Peak intensity 4.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED NF2x757G
FWHM / FWTM 26.0° / 44.0°
Efficiency 93 %
Peak intensity 4.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)