



RECOMMENDED P.C.B. LAYOUT  
安装尺寸图

规格 Specifications

额定负荷 Rating	DC 12V/50mA	
接触电阻 Contact Resistance	100mΩ max.	
绝缘电阻 Insulation resistance	DC:100V 60S 100MΩ min.	
抗电强度 Dielectric strength	AC:250V(50~60HZ) 60S min.	
操作力 Operation force	160±50gf	250±50gf
寿命试验 Operating Life	100,000 cycles	70,000 cycles
行程 Travels	0.25±0.1mm	

PRODUCT NO.: 1TS 005F\*\*\*\*-\*\*\*\*-\*\*\*\* CT

- 轻触开关
- 系列
- 外形:
- 按钮颜色:
- 底座颜色:
- 盖板颜色:
- 初始颜色, 则不启用
- 操作力度:
- 手感:
- 材质:
- 非编带
- 编带
- 非编带, 不启用
- 产品高度(H):
- 900=9.0mm

ITEM	PART NAME	QUANTITY	MATERIAL	FINISH
5	COVER	1	Stainless Steel	NATURAL
4	ACTUATOR	1	PPA	BLACK
3	DOVE	1	Phosphor Bronze/Ag	Ag-PLATED
2	TERMINAL	1	BRASS	Ag-PLATED
1	HOUSING	1	PPA	BLACK

X. ±	0.3	X. ±	3'	UNITS	MM
X. ±	0.2	X. ±	2'	MAT'L	
.XX ±	0.1	.XX ±	1'	FINISH	
.XXX ±	0.05	.XXX ±	0.5'		

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON YUAN PRECISION CO., LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON YUAN	Q'TY	DR.Y.Y.Chen	2015/08/10	SCALE	10/1	SHEET	2/2	REV.	A
--	------	-------------	------------	-------	------	-------	-----	------	---