



P.C.B Layout  
Top view

N=NUMBER OF POLES

DIM	TOL			
	1P--6P	7P--12P	13P--16P	
Dim P	(N-1)×7.5	±0.15	±0.25	±0.35
Dim L	N×7.5+1.8	±0.15	±0.25	±0.35

SIGN	DATE	DESCRIPTION	APPROVER
△	09/15`11	The color is changed from RAL7035/D to RAL7004/P	Runner
△	09/15`11	The dimension is changed from 2.1 to 2.2	Runner
△	09/15`11	The Material is changed	Runner
△	09/15`11	The tolerance is changed	Runner
△	09/25`13	change the dimension from 18.6&2.6 to 19.2&3.2	Da cheng
△	09/25`13	change the electrical specification	Da cheng

**THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!**

Material:

- Item ① Terminal body: Thermoplastic (UL94V-0)
- Item ② Terminal side body: Thermoplastic (UL94V-0)
- Item ③ Terminal cover: Thermoplastic (UL94V-0)
- Item ④ Contact pin : Copper, Tin Plated.
- Item ⑤ Spring clamp : Stainless steel

- △ Electrical: cULus
- Voltage rating: 300 V
  - Current rating(Sol): 30 A
  - Current rating(Str): 35 A
  - Solid wire(AWG): 10-24
  - Stranded wire(AWG): 8-24
  - Wire strip length: 15-16 mm
  - Withstanding Voltage: 1.6KV
  - Operating temperature: -40°C to +120°C
  - Soldering temperature: 260°C±5°C/5 Sec
  - Safety Approval:
  - Critical dimension: ▽

NK xx A 1 x 0 xxxx G

RoHS compliant  
(lead=4%)

In copper Alloy

- End Stackable
- 01: 1 POLES
  - 02: 2 POLES
  - 16: 16 POLES

△ Body Color

- 0 Black (RAL9005)
- 2 Red (RAL3001/D)
- 3 Orange(RAL2011/P)
- 4 Yellow(RAL1018/A)
- 5 Green(RAL6018/T)
- 6 Blue (RAL5015/A)
- △8 Grey(RAL7004/P)
- 9 White(RAL1102)
- C Multiple colors

0000: "@" Logo (Standard)  
000A: "ANYTEK" Mark  
Any special item by customer request, please contact sales department.

# ANYTEK

## CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		NK 7.5mm Series Right angle (Double tail A type)(平行脚)				
PART NO.	NKxxA1x0xxxxG	DWG NO.	8NK0003			
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance	
		Da cheng 2013.09.25	Da cheng 2013.09.25		UNIT: mm	X. ±0.50
				SHEET: 01/01	SCALE: NONE	X.X ±0.30
					REV.: C	X.XX ±0.10
						X° ±1°