

Inverter Grade Thyristors (Hockey PUK Version), 940 A



B-PUK (TO-200AC)



**RoHS
COMPLIANT**

FEATURES

- Metal case with ceramic insulator
- All diffused design
- Center amplifying gate
- Guaranteed high dV/dt
- Guaranteed high dI/dt
- International standard case B-PUK (TO-200AC)
- High surge current capability
- Low thermal impedance
- High speed performance
- Designed and qualified for industrial level
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

TYPICAL APPLICATIONS

- Inverters
- Choppers
- Induction heating
- All types of force-commutated converters

| PRIMARY CHARACTERISTICS | |
|-------------------------|------------------|
| Package | B-PUK (TO-200AC) |
| Circuit configuration | Single SCR |
| $I_{T(AV)}$ | 940 A |
| V_{DRM}/V_{RRM} | 400 V, 800 V |
| V_{TM} | 1.63 V |
| I_{TSM} at 50 Hz | 20 000 A |
| I_{TSM} at 60 Hz | 20 950 A |
| I_{GT} | 200 mA |
| T_C/T_{hs} | 55 °C |

| MAJOR RATINGS AND CHARACTERISTICS | | | |
|-----------------------------------|-----------------|-------------|-------------------|
| PARAMETER | TEST CONDITIONS | VALUES | UNITS |
| $I_{T(AV)}$ | | 940 | A |
| | T_{hs} | 55 | °C |
| $I_{T(RMS)}$ | | 1900 | A |
| | T_{hs} | 25 | °C |
| I_{TSM} | 50 Hz | 20 000 | A |
| | 60 Hz | 20 950 | |
| I^2t | 50 Hz | 2000 | kA ² s |
| | 60 Hz | 1820 | |
| V_{DRM}/V_{RRM} | | 400 to 800 | V |
| t_q | Range | 10 to 20 | µs |
| T_J | | -40 to +125 | °C |

ELECTRICAL SPECIFICATIONS

| VOLTAGE RATINGS | | | | |
|-----------------|--------------|--|--|--|
| TYPE NUMBER | VOLTAGE CODE | V_{DRM}/V_{RRM} , MAXIMUM REPETITIVE PEAK VOLTAGE V | V_{RSM} , MAXIMUM NON-REPETITIVE PEAK VOLTAGE V | I_{DRM}/I_{RRM} MAXIMUM AT $T_J = T_J$ MAXIMUM mA |
| VS-ST733C..L | 04 | 400 | 500 | 75 |
| | 08 | 800 | 900 | |



| CURRENT CARRYING CAPABILITY | | | | | | | |
|----------------------------------|-----------|------|-----------|------|-----------|------|----------------|
| FREQUENCY | | | | | | | UNITS |
| 50 Hz | 2200 | 1900 | 3580 | 3100 | 6800 | 5920 | A |
| 400 Hz | 2050 | 1660 | 3600 | 3130 | 3750 | 3240 | |
| 1000 Hz | 1370 | 1070 | 2900 | 2450 | 2120 | 1780 | |
| 2500 Hz | 500 | 370 | 1220 | 980 | 960 | 770 | |
| Recovery voltage V_R | 50 | | 50 | | 50 | | V |
| Voltage before turn-on V_D | V_{DRM} | | V_{DRM} | | V_{DRM} | | |
| Rise of on-state current di/dt | 50 | | - | | - | | A/ μ s |
| Heatsink temperature | 40 | 55 | 40 | 55 | 40 | 55 | $^{\circ}$ C |
| Equivalent values for RC circuit | 10/0.47 | | 10/0.47 | | 10/0.47 | | Ω/μ F |

| ABSOLUTE MAXIMUM RATINGS | | | | | | |
|--|---------------|--|----------------------------|---|----------------------------|-----------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VALUES | UNITS | |
| Maximum average on-state current at heatsink temperature | $I_{T(AV)}$ | 180 $^{\circ}$ conduction, half sine wave double side (single side) cooled | | 940 (350) | A | |
| | | | | 55 (85) | $^{\circ}$ C | |
| Maximum RMS on-state current | $I_{T(RMS)}$ | DC at 25 $^{\circ}$ C heatsink temperature double side cooled | | 1900 | | |
| Maximum peak, one half cycle, non-repetitive surge current | I_{TSM} | t = 10 ms t = 8.3 ms | No voltage reappplied | Sinusoidal half wave, initial $T_J = T_J$ maximum | 20 000 | A |
| | | | | | t = 10 ms t = 8.3 ms | |
| | | t = 10 ms t = 8.3 ms | No voltage reappplied | | | |
| | | | | | t = 10 ms t = 8.3 ms | |
| Maximum I^2t for fusing | I^2t | t = 10 ms t = 8.3 ms | No voltage reappplied | 2000 | | kA 2 s |
| | | | | t = 10 ms t = 8.3 ms | 100 % V_{RRM} reappplied | |
| | | t = 10 ms t = 8.3 ms | 100 % V_{RRM} reappplied | | | |
| | | | | t = 10 ms t = 8.3 ms | 100 % V_{RRM} reappplied | |
| Maximum $I^2\sqrt{t}$ for fusing | $I^2\sqrt{t}$ | t = 0.1 ms to 10 ms, no voltage reappplied | | | | 20 000 |
| Maximum peak on-state voltage | V_{TM} | $I_{TM} = 1700$ A, $T_J = T_J$ maximum, $t_p = 10$ ms sine wave pulse | | 1.63 | V | |
| Low level value of threshold voltage | $V_{T(TO)1}$ | $(16.7 \% \times \pi \times I_{T(AV)}) < I < \pi \times I_{T(AV)}$, $T_J = T_J$ maximum | | 1.09 | | |
| High level value of threshold voltage | $V_{T(TO)2}$ | $I > \pi \times I_{T(AV)}$, $T_J = T_J$ maximum | | 1.20 | | |
| Low level value of forward slope resistance | r_{t1} | $(16.7 \% \times \pi \times I_{T(AV)}) < I < \pi \times I_{T(AV)}$, $T_J = T_J$ maximum | | 0.32 | m Ω | |
| High level value of forward slope resistance | r_{t2} | $I > \pi \times I_{T(AV)}$, $T_J = T_J$ maximum | | 0.29 | | |
| Maximum holding current | I_H | $T_J = 25$ $^{\circ}$ C, $I_T > 30$ A | | 600 | mA | |
| Typical latching current | I_L | $T_J = 25$ $^{\circ}$ C, $V_A = 12$ V, $R_a = 6$ Ω , $I_G = 1$ A | | 1000 | | |

| SWITCHING | | | | | |
|--|---------|--|---|--------|------------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VALUES | UNITS |
| Maximum non-repetitive rate of rise of turned-on current | di/dt | $T_J = T_J$ maximum, $V_{DRM} =$ Rated V_{DRM} , $I_{TM} = 2 \times di/dt$ Gate pulse: 20 V 20 Ω , 10 μ s 0.5 μ s rise time | | 1000 | A/ μ s |
| Typical delay time | t_d | $T_J = 25$ $^{\circ}$ C, $V_{DM} =$ Rated V_{DRM} , $I_{TM} = 50$ A DC, $t_p = 1$ μ s Resistive load, gate pulse: 10 V, 5 Ω source | | 1.5 | μ s |
| Maximum turn-off time | minimum | t_q | $T_J = T_J$ maximum, $I_{TM} = 550$ A, commutating $di/dt = 40$ A/ μ s, $V_R = 50$ V, $t_p = 500$ μ s, dV/dt : see table in device code | 10 | |
| | maximum | | | 20 | |



| BLOCKING | | | | |
|--|-------------------------------------|--|--------|-------|
| PARAMETER | SYMBOL | TEST CONDITIONS | VALUES | UNITS |
| Maximum critical rate of rise of off-state voltage | dV/dt | T _J = T _J maximum, linear to 80 % V _{DRM} , higher value available on request | 500 | V/μs |
| Maximum peak reverse and off-state leakage current | I _{RRM} , I _{DRM} | T _J = T _J maximum, rated V _{DRM} /V _{RRM} applied | 75 | mA |

| TRIGGERING | | | | |
|---|--------------------|---|--------|-------|
| PARAMETER | SYMBOL | TEST CONDITIONS | VALUES | UNITS |
| Maximum peak gate power | P _{GM} | T _J = T _J maximum, f = 50 Hz, d% = 50 | 60 | W |
| Maximum average gate power | P _{G(AV)} | | 10 | |
| Maximum peak positive gate current | I _{GM} | T _J = T _J maximum, t _p ≤ 5 ms | 10 | A |
| Maximum peak positive gate voltage | +V _{GM} | | 20 | |
| Maximum peak negative gate voltage | -V _{GM} | | 5 | |
| Maximum DC gate current required to trigger | I _{GT} | T _J = 25 °C, V _A = 12 V, R _a = 6 Ω | 200 | mA |
| Maximum DC gate voltage required to trigger | V _{GT} | | 3 | |
| Maximum DC gate current not to trigger | I _{GD} | T _J = T _J maximum, rated V _{DRM} applied | 20 | mA |
| Maximum DC gate voltage not to trigger | V _{GD} | | 0.25 | |

| THERMAL AND MECHANICAL SPECIFICATIONS | | | | |
|--|---------------------|---|------------------|-----------|
| PARAMETER | SYMBOL | TEST CONDITIONS | VALUES | UNITS |
| Maximum operating junction temperature range | T _J | | -40 to +125 | °C |
| Maximum storage temperature range | T _{Stg} | | -40 to +150 | |
| Maximum thermal resistance, junction to heatsink | R _{thJ-hs} | DC operation single side cooled | 0.073 | K/W |
| | | DC operation double side cooled | 0.031 | |
| Maximum thermal resistance, case to heatsink | R _{thC-hs} | DC operation single side cooled | 0.011 | |
| | | DC operation double side cooled | 0.005 | |
| Mounting force, ± 10 % | | | 14 700 (1500) | N (kg) |
| Approximate weight | | | 255 | g |
| Case style | | See dimensions - link at the end of datasheet | B-PUK (TO-200AC) | |

| ΔR_{thJ-hs} CONDUCTION | | | | | | |
|---------------------------------------|-----------------------|-------------|------------------------|-------------|---|-------|
| CONDUCTION ANGLE | SINUSOIDAL CONDUCTION | | RECTANGULAR CONDUCTION | | TEST CONDITIONS | UNITS |
| | SINGLE SIDE | DOUBLE SIDE | SINGLE SIDE | DOUBLE SIDE | | |
| 180° | 0.009 | 0.009 | 0.006 | 0.006 | T _J = T _J maximum | K/W |
| 120° | 0.011 | 0.011 | 0.011 | 0.011 | | |
| 90° | 0.014 | 0.014 | 0.015 | 0.015 | | |
| 60° | 0.020 | 0.021 | 0.021 | 0.022 | | |
| 30° | 0.036 | 0.036 | 0.036 | 0.036 | | |

Note

- The table above shows the increment of thermal resistance R_{thJ-hs} when devices operate at different conduction angles than DC




Fig. 1 - Current Ratings Characteristics




Fig. 4 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 5 - On-State Power Loss Characteristics




Fig. 3 - Current Ratings Characteristics




Fig. 6 - On-State Power Loss Characteristics




Fig. 7 - Maximum Non-Repetitive Surge Current Single and Double Side Cooled




Fig. 10 - Thermal Impedance $Z_{th(jc)}$ Characteristics




Fig. 8 - Maximum Non-Repetitive Surge Current Single and Double Side Cooled




Fig. 11 - Reverse Recovered Charge Characteristics




Fig. 9 - On-State Voltage Drop Characteristics




Fig. 12 - Reverse Recovered Current Characteristics





Fig. 13 - Frequency Characteristics





Fig. 14 - Frequency Characteristics





Fig. 15 - Frequency Characteristics




Fig. 16 - Maximum On-State Energy Power Loss Characteristics





Fig. 17 - Gate Characteristics



ORDERING INFORMATION TABLE



- 1** - Vishay Semiconductors product
- 2** - Thyristor
- 3** - Essential part number
- 4** - 3 = fast turn-off
- 5** - C = ceramic PUK
- 6** - Voltage code x 100 = V_{RRM}
(see Voltage Ratings table)
- 7** - L = PUK case B-PUK (TO-200AC)
- 8** - Reapplied dV/dt code (for t_q test condition)
- 9** - t_q code
- 10** - 0 = eyelet terminals
(gate and auxiliary cathode unsoldered leads)
1 = fast-on terminals
(gate and auxiliary cathode unsoldered leads)
2 = eyelet terminals
(gate and auxiliary cathode soldered leads)
3 = fast-on terminals
(gate and auxiliary cathode soldered leads)
- 11** - Critical dV/dt:
 - None = 500 V/ μ s (standard value)
 - L = 1000 V/ μ s (special selection)

| dV/dt - t_q combinations available | | | | | | |
|--------------------------------------|--------------------|----|----|-----|-----|-----|
| | dV/dt (V/ μ s) | 20 | 50 | 100 | 200 | 400 |
| t_q (μ s) | 10 | CN | DN | EN | - | - |
| | 12 | CM | DM | EM | FM* | - |
| | 15 | CL | DL | EL | FL* | HL |
| | 18 | CP | DP | EP | FP | HP |
| | 20 | CK | DK | EK | FK | H |

* Standard part number.
All other types available only on request.


| LINKS TO RELATED DOCUMENTS | |
|----------------------------|--|
| Dimensions | www.vishay.com/doc?95076 |




B-PUK (TO-200AC)

DIMENSIONS in millimeters (inches)

Creepage distance: 36.33 (1.430) minimum
Strike distance: 17.43 (0.686) minimum



Note:
A = Anode
C = Cathode



Quote between upper and lower pole pieces has to be considered after application of mounting force (see thermal and mechanical specification)



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.