



CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	2-4 @20°C	0.031 ohms ±20%
D.C. RESISTANCE	8-7 @20°C	0.090 ohms ±20%
D.C. RESISTANCE	6-5 @20°C	0.070 ohms ±20%
INDUCTANCE	2-4 100kHz, 100mVAC, Ls	2.5uH ±10%
SATURATION CURRENT	20% Rolloff from initial	12A
LEAKAGE INDUCTANCE	2-4 tie(5+6+7+8), 100kHz, 10mVAC, Ls	125nH max.
DIELECTRIC	2-8 tie(6+7), 2500VAC, 1 second	2500VAC, 1 minute
DIELECTRIC	2-8 tie(6+7), 4000VDC, 1 second	-
URNS RATIO	(8-5):(2-4), tie(6+7)	2.5:1, ±1%
URNS RATIO	(8-7):(6-5)	1:1, ±1%



GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Safety Standard Undefined.

Wire insulation & RoHS status not affected by wire color.  
Wire insulation color may vary depending on availability.

DETAILS SUBJECT TO CHANGE

REV.	DATE	Packaging Specifications		Tolerances unless otherwise specified: Angles: ±1° Fractions: ±1/64	DRAWING TITLE <b>TRANSFORMER</b>	PART NO. <b>750311880</b>
6D	9/22	Method: Tape & Reel		Decimals: ±.005 [0.13]		
6C	7/18	PKG-0410		Footprint: ±.005 [0.13]		
6B	8/13	www.we-online.com/midcom		This drawing is dual dimensioned. Dimensions in brackets are in millimeters.		
6A	2/11	SEE REVISION SHEET FOR REVISION LEVEL				

