

Cable - FLK 40/4X14/EZ-DR/ 50/OB32

2296786

<https://www.phoenixcontact.com/us/products/2296786>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Round cable set; controller: Allen-Bradley SLC 500 (OB 32); connection 1: IDC/FLK socket strip (1x 40-position); connection 2: IDC/FLK socket strip (4x 14-position); cable length: 0.5 m

Your advantages

- System cable can be used to split 32 channels into 4 x 8 channels

Commercial Data

Item number	2296786
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	C02
Product Key	CK2141
Catalog Page	Page 475 (C-5-2019)
GTIN	4017918612870
Weight per Piece (including packing)	115.2 g
Weight per Piece (excluding packing)	115 g
Customs tariff number	85444290
Country of origin	DE

Technical Data

Product properties

Product type	System cable
Insulation characteristics	
Overvoltage category	II
Pollution degree	2
Insulation	Functional insulation

Ambient conditions

Degree of protection	IP00 ≥ IP54 (Installation location)
Ambient temperature (operation)	-40 °C ... 70 °C (fixed installation) -10 °C ... 70 °C (flexible installation)
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m

Electrical properties

Max. permissible operating voltage	25 V AC 60 V DC
Nominal operating mode	100% operating factor
Max. current carrying capacity per path	1 A (50 °C) 0.6 A (70 °C)
Rated insulation voltage	63 V
Rated surge voltage	0.6 kV

Supported controller ALLEN-BRADLEY SLC 500

Suitable I/O card	1746 OB 32 1746 OV 32
-------------------	--------------------------

Cable / line

Cable length	0.5 m
--------------	-------

10X0.14 [PVC]

UL AWM Style	2464/1061
Number of positions	10
Shielded	no
Cable type	10X0.14 [PVC]
Conductor type	Round cable set
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Conductor cross section	10x 0.14 mm ²
Wire diameter incl. insulation	1 mm ±0.03 mm
External cable diameter	6.1 mm ±0.4 mm

Cable - FLK 40/4X14/EZ-DR/ 50/OB32



2296786

<https://www.phoenixcontact.com/us/products/2296786>

Outer sheath, material	Semi-rigid PVC
External sheath, color	gray
Conductor material	Tin-plated Cu litz wires
Cable resistance	$\leq 145 \Omega/\text{km}$ (20 °C)
Insulation resistance	$\geq 20 \text{ M}\Omega \cdot \text{km}$ (20 °C)
Smallest bending radius, fixed installation	52 mm
Smallest bending radius, movable installation	98 mm
Max. bending cycles	5000
Halogen-free	no
Flame resistance	IEC 60332-1-2 (raw cable)
	VDE 0842, Part 332-1-2 (raw cable)
	IEC 60332-3-22 (raw cable)
	UL VW-1
	CSA FT-1
Resistance to oil	can withstand occasional splashes (raw cable)
Type	Splitting cable for four modules
Cable, preassembly	Insulation displacement, IEC 60352-4/DIN EN 60352-4

color code

IDC/FLK40 (5)	IDC/FLK14-1 (1) = black
IDC/FLK40 (7)	IDC/FLK14-1 (2) = brown
IDC/FLK40 (9)	IDC/FLK14-1 (3) = red
IDC/FLK40 (11)	IDC/FLK14-1 (4) = orange
IDC/FLK40 (13)	IDC/FLK14-1 (5) = yellow
IDC/FLK40 (15)	IDC/FLK14-1 (6) = green
IDC/FLK40 (17)	IDC/FLK14-1 (7) = blue
IDC/FLK40 (19)	IDC/FLK14-1 (8) = violet
IDC/FLK40 (1)	IDC/FLK14-1 (9) = gray
IDC/FLK40 (37)	IDC/FLK14-1 (10) = white
IDC/FLK40 (21)	IDC/FLK14-2 (1) = black
IDC/FLK40 (23)	IDC/FLK14-2 (2) = brown
IDC/FLK40 (25)	IDC/FLK14-2 (3) = red
IDC/FLK40 (27)	IDC/FLK14-2 (4) = orange
IDC/FLK40 (29)	IDC/FLK14-2 (5) = yellow
IDC/FLK40 (31)	IDC/FLK14-2 (6) = green
IDC/FLK40 (33)	IDC/FLK14-2 (7) = blue
IDC/FLK40 (35)	IDC/FLK14-2 (8) = violet
IDC/FLK40 (3)	IDC/FLK14-2 (9) = gray
IDC/FLK40 (39)	IDC/FLK14-2 (10) = white
IDC/FLK40 (6)	IDC/FLK14-3 (1) = black
IDC/FLK40 (8)	IDC/FLK14-3 (2) = brown
IDC/FLK40 (10)	IDC/FLK14-3 (3) = red
IDC/FLK40 (12)	IDC/FLK14-3 (4) = orange
IDC/FLK40 (14)	IDC/FLK14-3 (5) = yellow

IDC/FLK40 (16)	IDC/FLK14-3 (6) = green
IDC/FLK40 (18)	IDC/FLK14-3 (7) = blue
IDC/FLK40 (20)	IDC/FLK14-3 (8) = violet
IDC/FLK40 (2)	IDC/FLK14-3 (9) = gray
IDC/FLK40 (38)	IDC/FLK14-3 (10) = white
IDC/FLK40 (22)	IDC/FLK14-4 (1) = black
IDC/FLK40 (24)	IDC/FLK14-4 (2) = brown
IDC/FLK40 (26)	IDC/FLK14-4 (3) = red
IDC/FLK40 (28)	IDC/FLK14-4 (4) = orange
IDC/FLK40 (30)	IDC/FLK14-4 (5) = yellow
IDC/FLK40 (32)	IDC/FLK14-4 (6) = green
IDC/FLK40 (34)	IDC/FLK14-4 (7) = blue
IDC/FLK40 (36)	IDC/FLK14-4 (8) = violet
IDC/FLK40 (4)	IDC/FLK14-4 (9) = gray
IDC/FLK40 (40)	IDC/FLK14-4 (10) = white

Connection data

Field level

Connection in acc. with standard	IEC 60603-13
Connection method	IDC/FLK socket strip
Number of connections	4
Number of positions	14
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm

Controller level


Connection in acc. with standard	IEC 60603-13
Connection method	IDC/FLK socket strip
Number of connections	1
Number of positions	40
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm

Standards and regulations

Air clearances and creepage distances

Standards/regulations	DIN EN 50178
-----------------------	--------------

Drawings



Maximum permissible current per path in uncoiled state

Cable - FLK 40/4X14/EZ-DR/ 50/OB32

2296786

<https://www.phoenixcontact.com/us/products/2296786>



Approvals



EAC

Approval ID: RU*-DE.HB*35.B00385



UL Listed

Approval ID: FILE E 238705

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	125 V	1 A	-	-



cUL Listed

Approval ID: FILE E 238705

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	125 V	1 A	-	-

cULus Listed

Cable - FLK 40/4X14/EZ-DR/ 50/OB32



2296786

<https://www.phoenixcontact.com/us/products/2296786>

Classifications

ECLASS

ECLASS-9.0	27242220
ECLASS-10.0.1	27242220
ECLASS-11.0	27242220

ETIM

ETIM 8.0	EC000237
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

Cable - FLK 40/4X14/EZ-DR/ 50/OB32



2296786

<https://www.phoenixcontact.com/us/products/2296786>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Cable - FLK 40/4X14/EZ-DR/ 50/OB32

2296786

<https://www.phoenixcontact.com/us/products/2296786>



Accessories

Cable marker carrier

Cable marker carrier - KME - 0807083

<https://www.phoenixcontact.com/us/products/0807083>



Cable marker carrier, white, unlabeled, mounting type: Assembly with cable ties, cable diameter: > 5 mm, lettering field size: 20 mm x 8 mm

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com