


Pressure switches - Vacuum



Pressure switches - vacuum (electrical output)


- Conform to the Low Voltage Directive
- Can be used without enclosure according to IEC 664-1 pollution group III



Part numbers

Pressure and vacuum switches	81 513 552	81 513 502	81 513 501	81 513 522
Mounting	DIN rail	DIN rail	DIN rail	DIN rail
Actuators	Pressure with	Pressure without	Low pressure without	Vacuum without
Manual override				

Symbol



Characteristics

Pneumatic connection	Push-in connection for semi-rigid tubing (NFE 49100) Tapped BSP via connector	mm	Ø 4 ext.	Ø 4 ext.	Ø 4 ext.	Ø 4 ext.
Protection	IEC 529		IP 20	IP 20	IP 20	IP 20
Permissible fluid: air, inert gases and liquids			●	●	●	●
Adjustment of switching pressure (* adjusted to 0.3)	bar		2 → 8	2 → 8	0.3 → 1.2 *	-0.3 → -0.8
Hysteresis						
at 1 bar	bar		0.5	0.5	—	—
at 2 bars	bar		0.6	0.6	—	—
at 4 bars	bar		0.8	0.8	—	—
at 6 bars	bar		1	1	—	—
max. 200 mb			—	—	●	—
max. 250 mb			—	—	—	●
Pressure to break			—	—	—	—
Mechanical life (operations)			10 ⁶	10 ⁶	10 ⁶	10 ⁶
Contact rating (V resistive)			5A - 220-230 V	5A - 220-230 V	5A - 220-230 V	5A - 220-230 V
Wire cross-section	mm ²		0.75	0.75	0.75	0.75
Operating temperature	°C		-10 → +70	-10 → +70	-10 → +70	-10 → +70
Weight	g		48	46	46	46
Standard electrical contact			V4 83 170 4 W2	V4 83 170 4 W2	V4 83 170 4 W2	V4 83 170 4 W2
UL and cUL approval			MH15213 (R)	MH15213 (R)	MH15213 (R)	MH15213 (R)




Operation

Pressure operated

Vacuum operated

Electrical life

(Crouzet microswitch "V4" ref 83 170 4-1-W2)






For continuous vacuum applications, please consult us.


Other information

On request :

- Microswitch V4 ref. 83 170 0 i W2 high current
- Microswitch V4 ref. 83 170 9 i W2 low current



81 513 516	81 513 510	81 513 527		81 513 533	81 513 523		81 509 080	81 509 085
Base mounted page 4/14	Base mounted page 4/14	Base mounted page 4/14		2 screws M4	2 screws M4		Base mounted page 4/14	Base mounted page 4/14
Pressure without	Pressure with	Vacuum without		Pressure without	Vacuum without		Pressure without	Pressure with




Ø 4 ext.	Ø 4 ext.	Ø 4 ext.						
IP 54	IP 54	IP 54		1/8 BSP IP 54	1/8 BSP IP 54		Via sub-base IP 54	Via sub-base IP 54
2 → 8	2 → 8	-0.3 → -0.9		2 → 8	-0.3 → -0.8		1.4 ± 0.5	1.4 ± 0.5
0.5	0.5	—		0.5	—		—	—
0.6	0.6	—		0.6	—		—	—
0.8	0.8	—		0.8	—		—	—
1	1	—		1	—		—	—
—	—	—		—	—		—	—
—	—	—		—	—		—	—
10 ⁶	10 ⁶	10 ⁶		10 ⁶	10 ⁶		0.6 ± 0.2	0.6 ± 0.2
5A - 220-230 V	5A - 220-230 V	5A - 220-230 V		5A - 220-230 V	5A - 220-230 V		10 ⁶	10 ⁶
0.75	0.75	0.75		0.75	0.75		5A - 220-230 V	5A - 220-230 V
-10 → +70	-10 → +70	-10 → +70		-10 → +70	-10 → +70		1.5	1.5
56	58	56		65	65		-10 → +70	-10 → +70
V4 83 170 4 W2	V4 83 170 4 W2	V4 83 170 4 W2		V4 83 170 4 W2	V4 83 170 4 W2		80	80
MH15213 (R)	MH15213 (R)	MH15213 (R)		MH15213 (R)	MH15213 (R)		83 133 004	83 133 004


Electrical connections
81 513 501 - 81 513 502
81 513 522 - 81 513 552

Dimensions
81 513 552 - 81 513 502
81 513 501 - 81 513 522


Pressure switch with connector
81 513 516 - 81 513 510
81 513 527
81 516 082
81 513 533
81 513 523




81 513 510
81 513 516 - 81 513 527



81 513 533
81 513 523 - 81 513 533



81 509 080 - 81 509 085




Adjustable pressure switches (manostats) (pneumatic output)

■ 100 % pneumatic





Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



Part numbers (and adjustment ranges)

Adjustment range	50 → 500 mb 0.1 → 2.5 b 2 → 8 b	81 505 140 81 505 150 81 505 160	81 502 140 81 502 150 81 502 160
Version		Positive output	Negative output
Accuracy	50 → 500 mb 0.1 → 2.5 b 2 → 8 b	10 % 4 % 4 %	10 % 4 % 4 %

Symbol




Characteristics

Orifice diameter	mm	2.5	2.5
Flow at 4 bars	NI/min	170	170
Hysteresis	50 → 500 mb 0.1 → 2.5 b 2 → 8 b	60 mb 100 mb 320 mb	60 mb 100 mb 320 mb
Connection - sub-base pages 54/55		●	●
Operating temperature	°C	-5 → +50	-5 → +50
Mechanical life	operations	3 x 10 ⁶	3 x 10 ⁶
Weight	g	160	160

Connections



Example of pressure threshold adjustment (mini-regulator - manostat)





Principle of operation

The manostats provide an on or off output signal when the input signal reaches a predetermined pressure threshold.

Positive output




Negative output



Dimensions

81 502 140 - 81 502 150 - 81 502 160
81 505 140 - 81 505 150 - 81 505 160




Other information Pressure switches with electrical output on request.

ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Adjustable vacuum switches (vacuostat)

- 100 % pneumatic
- For vacuum -0,1 → -0,9 Bar



Part numbers

81 505 110

Positive output




81 502 110

Negative output

81 508 110

Electrical output

Symbol




Characteristics

Adjustment range	b	- 0.1 → -0.9	- 0.1 → -0.9	- 0.1 → -0.9
Flow at 6 bars	NI/min	170	170	170
Hysteresis	mb	80	80	80
Connection - sub-base pages 54/55		•	•	•
Operating temperature	°C	-5 → +50	-5 → +50	-5 → +50
Mechanical life	operations	3 x 10 ⁶	3 x 10 ⁶	3 x 10 ⁶
Weight	g	160	160	180

Connections



Example of use:
Vacuum handling (vacuum generator, vacuum pad, vacuostats).





Principle of operation

Vacuostats provide an on or off output signal when the input signal reaches a predetermined pressure threshold.

Positive output




Negative output




Dimensions

81 502 110 - 81 505 110



81 508 110



Vacuum handling components

- Sur le principe du Venturi
- Facilement raccordable



Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive




Part numbers

Vacuum generators

81 535 301
Sub-base mounting

81 545 001
Plug-in


81 545 005
Plug-in



Characteristics

Push-in connectors for semi-rigid tubing (NFE 49100)	Male/Female/Female (MFF) Female/Female/Female (FFF)	—	Ø 4 mm	—
Operating pressure	bar	2 → 8	2 → 8	2 → 8
Vacuum pad material		—	—	—
Weight	g	80	13	25


Detection of the pressure decrease can be achieved by the use of manostats (see pages 38/39)




Dimensions

81 535 301


Sub-base mounting 81 531... and 81 532...



81 545 001



81 545 005



ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Crouzet:

[81502160](#) [81513502](#) [81513552](#) [81505140](#) [81513523](#) [81513612](#) [81502110](#) [81513509](#) [81508110](#) [81505160](#)
[81513527](#) [81513530](#) [81513535](#) [81502150](#) [81505150](#) [81513516](#) [81513533](#) [81513501](#) [81513510](#) [81535301](#)
[81545001](#) [81545005](#) [81502140](#) [81513522](#) [81505110](#) [81509080](#) [81509081](#)