

Basic terminal block - PI-TB

2835943

<https://www.phoenixcontact.com/us/products/2835943>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Base terminal block for non intrinsically safe signals with knife disconnection and test connections.

Commercial Data

Item number	2835943
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	C03
Product Key	CK38ZZ
Catalog Page	Page 467 (IF-2009)
GTIN	4017918911812
Weight per Piece (including packing)	95.29 g
Weight per Piece (excluding packing)	92.75 g
Customs tariff number	85369010
Country of origin	DE

Basic terminal block - PI-TB

2835943

<https://www.phoenixcontact.com/us/products/2835943>



Technical Data


Product properties

Product type	Module carrier
Application	Base element

Electrical properties

Nominal voltage U_N	250 V
Nominal current I_N	4 A

Dimensions

Dimensional drawing	
Width	12.4 mm
Height	145 mm
Depth	86.5 mm
Depth NS 35/7,5	147 mm (with NS 35/7.5 coupling connector)

Material specifications

Flammability rating according to UL 94	V0
Housing insulation material	PBT

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

Mounting

Mounting type	DIN rail mounting
---------------	-------------------

Basic terminal block - PI-TB


2835943

<https://www.phoenixcontact.com/us/products/2835943>



Drawings

Dimensional drawing



Basic terminal block - PI-TB

2835943

<https://www.phoenixcontact.com/us/products/2835943>



Approvals



EAC

Approval ID: RU*DE.*09.B.00387/20

Basic terminal block - PI-TB

2835943

<https://www.phoenixcontact.com/us/products/2835943>



Classifications

ECLASS

ECLASS-9.0	27141152
ECLASS-10.0.1	27141152
ECLASS-11.0	27141152

ETIM

ETIM 8.0	EC002780
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Basic terminal block - PI-TB

2835943

<https://www.phoenixcontact.com/us/products/2835943>



Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Basic terminal block - PI-TB

2835943

<https://www.phoenixcontact.com/us/products/2835943>



Accessories



Note: Applying some accessories below might limit this product.

Continuous plug-in bridge

Continuous plug-in bridge - FBST 500-PLC RD - 2966786

<https://www.phoenixcontact.com/us/products/2966786>



Continuous plug-in bridge, color: red




Max. current carrying capacity: 32 A

Continuous plug-in bridge

Continuous plug-in bridge - FBST 500-PLC BU - 2966692

<https://www.phoenixcontact.com/us/products/2966692>



Continuous plug-in bridge, color: blue



Max. current carrying capacity: 32 A

Basic terminal block - PI-TB

2835943

<https://www.phoenixcontact.com/us/products/2835943>



Continuous plug-in bridge

Continuous plug-in bridge - FBST 500-PLC GY - 2966838

<https://www.phoenixcontact.com/us/products/2966838>



Continuous plug-in bridge, color: gray

 Max. current carrying capacity: 32 A

Bridging module

Bridging module - PI-N-BRIDGE - 2835875

<https://www.phoenixcontact.com/us/products/2835875>



Bridging module, for bridging input and output circuit

Basic terminal block - PI-TB

2835943

<https://www.phoenixcontact.com/us/products/2835943>



Insulating sleeve

Insulating sleeve - MPS-IH RD - 0201676

<https://www.phoenixcontact.com/us/products/0201676>

Insulating sleeve, color: red




Insulating sleeve

Insulating sleeve - MPS-IH BU - 0201689

<https://www.phoenixcontact.com/us/products/0201689>

Insulating sleeve, color: blue



Basic terminal block - PI-TB

2835943

<https://www.phoenixcontact.com/us/products/2835943>



Insulating sleeve

Insulating sleeve - MPS-IH GY - 0201728

<https://www.phoenixcontact.com/us/products/0201728>

Insulating sleeve, color: gray



Screwdriver

Screwdriver - SZG 0,6X3,5 VDE - 1205121

<https://www.phoenixcontact.com/us/products/1205121>

Screwdriver, slot-headed, graded, for test socket screws, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip



Basic terminal block - PI-TB

2835943

<https://www.phoenixcontact.com/us/products/2835943>



Separating plate

Separating plate - PI-ATP - 2835969

<https://www.phoenixcontact.com/us/products/2835969>

Separating plate, 2 mm thick, black, required at the start and end of a PI terminal strip where continuous bridges are used.



Flat zack marker sheet

Flat zack marker sheet - ZBFM 6/WH:UNBEDRUCKT - 0803618

<https://www.phoenixcontact.com/us/products/0803618>

Flat zack marker sheet, Sheet, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5 x 5.5 mm, Number of individual labels: 100



Basic terminal block - PI-TB

2835943

<https://www.phoenixcontact.com/us/products/2835943>



Zack marker strip

Zack marker strip - ZBFM 6/WH,LGS:1-100 - 0800284

<https://www.phoenixcontact.com/us/products/0800284>

Zack marker strip, Sheet, white, labeled, printed horizontally: consecutive numbers from 1 ... 100, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5 x 5.5 mm, Number of individual labels: 100



Flat zack marker sheet

Flat zack marker sheet - ZBFM 6/WH,LGS:FORTL.ZAHLEN - 0803621

<https://www.phoenixcontact.com/us/products/0803621>

Flat zack marker sheet, Sheet, white, labeled, printed horizontally: consecutive numbers from 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snap into flat marker groove, for terminal block width: 6.2 mm, lettering field size: 5 x 5.5 mm, Number of individual labels: 100



Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com