

Limit value switches - MCR-PSP



2811912

<https://www.phoenixcontact.com/us/products/2811912>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

MCR threshold value switch, programmable, with 2 relay contacts



Your advantages

- This product is no longer available, please see the recoding list in the download area under "Miscellaneous"

Commercial Data

Item number	2811912
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	C01
Product Key	CK1843
Catalog Page	Page 138 (C-7-2015)
GTIN	4017918107888
Weight per Piece (including packing)	297.9 g
Weight per Piece (excluding packing)	297.9 g
Customs tariff number	85437090
Country of origin	DE

Technical Data

Notes

Utilization restriction

EMC note	EMC: class A product, see manufacturer's declaration in the download area
----------	---

Product properties

Product type	Threshold value switch
No. of channels	1
Display resolution	0,1 °C / 0,01 V / 0,01 mA / 0,1 Ω

Electrical properties

No. of channels	1
Measuring rate	2 Hz
Protective circuit	Transient protection, polarity protection
Maximum temperature coefficient	≤ 0.01 %/K
Maximum transmission error	0.1 % (of final value)

Supply

Supply voltage range	20 V DC ... 30 V DC
Max. current consumption	< 60 mA

Input data

Signal:

Configurable/programmable	Yes, programmable
Voltage input signal	-30 V ... 30 V
Current input signal	-30 mA ... 30 mA
Available input sources	Resistance temperature detectors in 2-, 3- or 4-conductor technology (in accordance with DIN 43760/DIN IEC 751 or SAMA RC 21-4-1966), e.g., PT sensors, Ni sensors, etc. Thermocouple sensors (in acc. with DIN IEC 584-1/DIN 43710): B, E, J, K, L, N, R, S, T, U Resistance: 0 kΩ ... 8 kΩ (2-conductor circuit only) Current: - 30 mA...+ 30 mA Voltage: - 30 V...+ 30 V
Input resistance of voltage input	200 kΩ
Input resistance current input	50 Ω
Discontinuous control resolution	0,1 °C / 0,01 V / 0,01 mA / 0,1 Ω

Measurement

Sensor type:	-200 °C ... 850 °C (freely adjustable)
	-200 °C ... 850 °C (freely adjustable)
	-200 °C ... 850 °C (freely adjustable)
	-200 °C ... 850 °C (freely adjustable)

Limit value switches - MCR-PSP



2811912

<https://www.phoenixcontact.com/us/products/2811912>

	-200 °C ... 850 °C (freely adjustable)
	-60 °C ... 180 °C (freely adjustable)
	-60 °C ... 180 °C (freely adjustable)
	-60 °C ... 180 °C (freely adjustable)
	-60 °C ... 180 °C (freely adjustable)
	-60 °C ... 180 °C (freely adjustable)
	-50 °C ... 160 °C (freely adjustable)
	-70 °C ... 500 °C (freely adjustable)
	-200 °C ... 600 °C (freely adjustable)
	-200 °C ... 400 °C (freely adjustable)
	-200 °C ... 900 °C (freely adjustable)
	-210 °C ... 1200 °C (freely adjustable)
	-226 °C ... 1000 °C (freely adjustable)
	-200 °C ... 1372 °C (freely adjustable)
	-200 °C ... 1300 °C (freely adjustable)
	-50 °C ... 1768 °C (freely adjustable)
	-50 °C ... 1768 °C (freely adjustable)
	500 °C ... 1820 °C (freely adjustable)
Linear resistance measuring range	0 Ω ... 8000 Ω

Output data

Switching:

Contact type	2 x changeover contacts / 2 switching points each, de-energized/energized (switchable)
Contact material	AgNi 0,15 + HTV (hard gold-plated)
Maximum switching voltage	250 V AC
Max. switching current	2 A AC
Mechanical service life	2x 10 ⁷ cycles
Setting range of the response delay	0 s ... 2 s (adjustable)
Status display	LED display

Connection data

Connection method	Pluggable screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section solid	0.2 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 14

LED signaling

Status display	5-position 7-segment display and LEDs
----------------	---------------------------------------

Dimensions


Limit value switches - MCR-PSP



2811912

<https://www.phoenixcontact.com/us/products/2811912>

Dimensional drawing



Width	45 mm
Height	75 mm
Depth	110 mm

Material specifications

Housing material	ABS
------------------	-----

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C ... 65 °C
---------------------------------	------------------

Approval data

CE

Certificate	CE-compliant
-------------	--------------

UL, USA / Canada

Identification	cULus
----------------	-------

EMC data

Noise emission	EN 61000-6-4
Noise immunity	EN 61000-6-2:2005

Mounting

Mounting type	DIN rail mounting
Mounting position	any

Limit value switches - MCR-PSP


2811912

<https://www.phoenixcontact.com/us/products/2811912>




Drawings

Dimensional drawing



Circuit diagram



Limit value switches - MCR-PSP



2811912

<https://www.phoenixcontact.com/us/products/2811912>

Classifications

ECLASS

ECLASS-9.0	27210120
ECLASS-10.0.1	27210120
ECLASS-11.0	27210120

Limit value switches - MCR-PSP

2811912

<https://www.phoenixcontact.com/us/products/2811912>



Accessories

Cable

Cable - CM-KBL-RS232/USB - 2881078

<https://www.phoenixcontact.com/us/products/2881078>

Connecting cable D-9-SUB to USB, with adapter D-9-SUB to D-25-SUB.



Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com