


Inline function terminal - IB IL TEMPCON RTD



2819244

<https://www.phoenixcontact.com/us/products/2819244>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Inline temperature controller, without accessories, 6 inputs for resistance temperature detectors, 6 outputs, 24 V DC, 3-conductor connection technology

Your advantages


- Configuration via engineering tool (configuration software)
- Self-tuning
- 6 outputs, 24 V DC / 70 mA
- Can be configured as a 2-step controller, 3-step controller, motor step controller or signaling device (threshold value switch)
- 6 analog inputs for Pt 100 according to DIN EN 60751
- Heating current and closed-loop control circuit monitoring

Commercial Data

Item number	2819244
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	00
Product Key	DRI191
Catalog Page	Page 243 (AX-2004)
GTIN	4017918890407
Weight per Piece (including packing)	157.6 g
Weight per Piece (excluding packing)	130.61 g
Customs tariff number	85389091
Country of origin	DE

Technical Data

Dimensions

Dimensional drawing	
Width	48.8 mm
Height	119.8 mm
Depth	71.5 mm

Interfaces

Inline local bus

Connection method	Inline data jumper
Transmission speed	500 kbps

System properties

Module

ID code (dec.)	191
ID code (hex)	BF
Length code (hex)	02
Length code (dec)	02
Process data channel	32 Bit
Input address area	4 Byte
Output address area	4 Byte
Register length	32 Bit
Required parameter data	1 Byte

Output data

Output current	70 mA
----------------	-------

Product properties

Type	modular
Product type	I/O component
No. of channels	6

Electrical properties

No. of channels	6
Test section	5 V supply, incoming remote bus/7.5 V supply (bus logics) 500 V AC 50 Hz 1 min.

Inline function terminal - IB IL TEMPCON RTD



2819244

<https://www.phoenixcontact.com/us/products/2819244>

	5 V supply, outgoing remote bus/7.5 V supply (bus logics) 500 V AC 50 Hz 1 min.
	7.5 V supply (bus logics)/24 V supply (I/O) 500 V AC 50 Hz 1 min.
	24 V supply (I/O) / functional ground 500 V AC 50 Hz 1 min.
	Analog inputs/bus logics 500 V AC 50 Hz 1 min.
	Analog inputs/24 V supply (I/O) 500 V AC 50 Hz 1 min.
	Analog inputs/functional ground 500 V AC 50 Hz 1 min.

Supply

Max. current consumption	4 A
Typical current consumption	250 mA

Connection data

Connection method	Spring-cage connection
-------------------	------------------------

Ambient conditions


Degree of protection	IP20
----------------------	------

Mounting


Mounting type	DIN rail mounting
---------------	-------------------

Drawings

Connection diagram



Dimensional drawing



Inline function terminal - IB IL TEMPCON RTD

2819244

<https://www.phoenixcontact.com/us/products/2819244>



Accessories

Inline shield connector

Inline shield connector - IB IL SCN 6-SHIELD-TWIN - 2740245

<https://www.phoenixcontact.com/us/products/2740245>

Inline shield connector



Inline connector

Inline connector - IB IL SCN-8 - 2726337

<https://www.phoenixcontact.com/us/products/2726337>

Connector, for digital 1, 2 or 8-channel Inline terminals



Inline function terminal - IB IL TEMPCON RTD



2819244

<https://www.phoenixcontact.com/us/products/2819244>

Labeling field

Labeling field - IB IL FIELD 8 - 2727515

<https://www.phoenixcontact.com/us/products/2727515>

Labeling field, width: 48.8 mm



Insert strip

Insert strip - ESL 62X46 - 0809502

<https://www.phoenixcontact.com/us/products/0809502>

Insert strip, Sheet, white, unlabeled, can be labeled with: Office printing systems:
Laser printer, mounting type: insert, lettering field size: 62 x 46 mm, Number of
individual labels: 15



Inline function terminal - IB IL TEMPCON RTD



2819244

<https://www.phoenixcontact.com/us/products/2819244>

License key

License key - IB IL TEMPCONTROL - 2819370

<https://www.phoenixcontact.com/us/products/2819370>

License key for using the engineering tools for the multi-channel process controllers of type: IB IL TEMPCON 300, including interface cable TEMPCON CAB-V24. The software must also be downloaded.



Interface cable

Interface cable - TEMPCON CAB-V24 - 2819419

<https://www.phoenixcontact.com/us/products/2819419>

Interface cable for Inline temperature controllers (IB IL TEMPCON ...), single



Inline function terminal - IB IL TEMPCON RTD



2819244

<https://www.phoenixcontact.com/us/products/2819244>

Labeling field

Labeling field - IB IL FIELD 2 - 2727501

<https://www.phoenixcontact.com/us/products/2727501>

Labeling field, width: 12.2 mm



Insert strip

Insert strip - ESL 62X10 - 0809492

<https://www.phoenixcontact.com/us/products/0809492>

Insert strip, Sheet, white, unlabeled, can be labeled with: Office printing systems:
Laser printer, mounting type: insert, lettering field size: 62 x 10 mm, Number of
individual labels: 72



Inline function terminal - IB IL TEMPCON RTD



2819244

<https://www.phoenixcontact.com/us/products/2819244>

User manual

User manual - IB IL TEMPCON FUNCTION UM E - 2698821

<https://www.phoenixcontact.com/us/products/2698821>



User manual, English, for setting the controller functions of Inline temperature controllers, only available as a download.

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com