

Insert label - EMT (50/28X13)R



0800049

<https://www.phoenixcontact.com/us/products/0800049>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Insert label, For marking Siemens ET 200S controllers, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting type: insert, lettering field size: 1 x 50 mm x 13 mm and 1 x 28 mm x 13 mm, Number of individual labels: 500

Your advantages

- EMT (50/28x13)R, white insert label, for marking Siemens ET 200S controllers
- Thanks to their special shape, the EMT (50/28x13)R insert labels remain securely inside the collar of the Siemens controller once inserted
- Quick and inexpensive marking with THERMOMARK ... roll printers from Phoenix Contact
- When combined with the right ink ribbon, the marking is highly resistant to solvents and mechanical influences. The marking is even suitable for use under harsh industrial conditions
- Marking service: Phoenix Contact can custom-mark all EMT ... markers according to your requirements

Commercial Data

Item number	0800049
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	B12
Product Key	BG2411
Catalog Page	Page 343 (C-3-2019)
GTIN	4046356545440
Weight per Piece (including packing)	273.4 g
Weight per Piece (excluding packing)	270 g
Customs tariff number	39269097
Country of origin	DE

Insert label - EMT (50/28X13)R



0800049

<https://www.phoenixcontact.com/us/products/0800049>

Technical Data

Product properties

Product type	Device marking
Controller type	For marking Siemens ET 200S controllers

Marking

Number of individual labels	500
Number of individual labels per row	2

Marking technology

Device	5146477 THERMOMARK ROLL
	5145274 THERMOMARK X1.1
	5146231 THERMOMARK X1.2
Printability	Thermal transfer

Ambient conditions

Ambient temperature (operation)	-40 °C ... 120 °C
Recommended storage conditions	23 °C / 50 % relative humidity

Mounting

Mounting type	insert
---------------	--------

Material specifications

Color	white
Foil strength	175 µm
Material	Polyester
Components	free from silicone and halogen
Silicone-free	yes
Halogen-free	Yes

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

	VDMA 24364-A1-L:2018-05
Result	Test passed

Scratch test for the determining scratch resistance

Requirements	≥ 5 N
Result	Test passed

Tesafilm test

Result	Test passed
--------	-------------

UV resistance

Specification	Following ISO 4892-2:2013-03
---------------	------------------------------

Insert label - EMT (50/28X13)R



0800049

<https://www.phoenixcontact.com/us/products/0800049>

Result	Test passed
Test duration	96 h

Temperature resistance

Specification	Following ANSI/UL 969-2018:03
Test duration	240 h
Rating 200 °C (230 °C)	Test passed

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-01):2020-03 DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Test duration	168 h

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1,0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

Ambient conditions

Ambient temperature (operation)	-40 °C ... 120 °C
Recommended storage conditions	23 °C / 50 % relative humidity
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %

Dimensions

Width	77.5 mm
Length	12.8 mm

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Insert label - EMT (50/28X13)R



0800049

<https://www.phoenixcontact.com/us/products/0800049>

Classifications

ECLASS

ECLASS-9.0	27400629
ECLASS-10.0.1	27400629
ECLASS-11.0	27281106

ETIM

ETIM 8.0	EC001530
----------	----------

UNSPSC

UNSPSC 21.0	39131700
-------------	----------

Insert label - EMT (50/28X13)R

0800049

<https://www.phoenixcontact.com/us/products/0800049>



Accessories

Ink ribbon

Ink ribbon - THERMOMARK-RIBBON 110-WMTB HF - 5148007

<https://www.phoenixcontact.com/us/products/5148007>



Ink ribbon, for roll printer for printing product groups WMTB HF..., WMS-2 HF..., TMT..., EMT..., EMLF..., PML-..., width: 110 mm, color: black

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com