

# I/O module - IB ST 24 BAO 8/U

2721044

<https://www.phoenixcontact.com/us/products/2721044>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



INTERBUS-ST analog output module, D/A resolution 13-bit, 8 outputs, -10 V to +10 V, -12 to +12 V, consisting of: Terminal part with screw connection and module electronics

## Product Description

### INTERBUS ST standard analog output modules

These 8-channel output modules are an inexpensive alternative in applications with many analog actuators.

In addition to the standard output voltage of -10 to +10 V, the IB ST 24 BAO 8/U offers an extended output range of -12 to +12 V.

If the high 12-bit resolution of the output value is not necessary, the IB ST 24 BAO 8B gives you the option of saving PLC memory by combining two channels of 8 bits each into one data word. Further features are:

- Diagnostic LEDs provide information on the operating status at any time.
- All modules can be individually labeled on the large pull-out labeling field. The insert cards can be prepared by hand, or by plotter or printer.
- In the event of failure or malfunction, the electronics of the module can be easily replaced. The passive termination block remains mounted on the rail. This means that the replacement process can be carried out in a just a few seconds and without the need for tools.
- The fuses are accessible from outside, so that a fault can be cleared quickly.
- The connection to protective earth ground is made directly via the DIN rail.
- The conventional labeling materials (Zack strip ZB-6, etc.) can be used to label the termination blocks.

## Your advantages

- Temperature measurement modules
- Standard signal types (voltage and current)

## Commercial Data

Item number	2721044
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	C21
Product Key	DRI342
Catalog Page	Page 251 (C-8-2013)
GTIN	4017918132316
Weight per Piece (including packing)	647.9 g
Weight per Piece (excluding packing)	600 g
Customs tariff number	85389091
Country of origin	DE

# I/O module - IB ST 24 BAO 8/U

2721044

<https://www.phoenixcontact.com/us/products/2721044>



## Technical Data

### Dimensions

Dimensional drawing	
Width	118 mm
Height	117 mm
Length	116 mm

### Notes

Utilization restriction	
EMC note	EMC: class A product, see manufacturer's declaration in the download area

### Interfaces

ST local bus	
Connection method	ST local bus connector
Transmission speed	500 kbps

### Product properties

Type	modular
	INTERBUS Smart Terminal
Product type	I/O component
No. of channels	8

### Electrical properties

No. of channels	8
Maximum power dissipation for nominal condition	3.6 W
Test section	Bus/Outputs 500 V AC 50 Hz 1 min. Supply voltage/Outputs 500 V AC 50 Hz 1 min. Supply voltage/Ground conductor 500 V AC 50 Hz 1 min. I/O voltage/Ground conductor 500 V AC 50 Hz 1 min.

### Supply

Communications power $U_L$	9 V DC (from the ST local bus)
I/O voltage	$\pm 24$ V DC 5 % (ripple)
I/O voltage range	18.5 V DC ... 30.2 V DC
Typical current consumption	150 mA (at Us)

# I/O module - IB ST 24 BAO 8/U

2721044

<https://www.phoenixcontact.com/us/products/2721044>



## Connection data

### Connection technology

Connection name	Termination block
-----------------	-------------------

#### Conductor connection

Connection method	Screw connection
Conductor cross section solid	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 12
Stripping length	8 mm

#### Termination block

Connection method	Screw connection
Conductor cross section, rigid	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section, flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 12
Stripping length	8 mm

## Ambient conditions

Degree of protection	IP20
----------------------	------

## Mounting

Mounting type	DIN rail mounting
---------------	-------------------

# I/O module - IB ST 24 BAO 8/U


2721044

<https://www.phoenixcontact.com/us/products/2721044>




## Drawings

Connection diagram



Dimensional drawing



# I/O module - IB ST 24 BAO 8/U

2721044

<https://www.phoenixcontact.com/us/products/2721044>



## Classifications

### ECLASS

ECLASS-9.0

27242601

# I/O module - IB ST 24 BAO 8/U

2721044

<https://www.phoenixcontact.com/us/products/2721044>




## Accessories

### Bridge

Bridge - IB ST LBC - 2836492

<https://www.phoenixcontact.com/us/products/2836492>

Spare local bus cable, for INTERBUS-ST modules



---

### Fuse

Fuse - IBS TR5 0,4AT - 2753478

<https://www.phoenixcontact.com/us/products/2753478>

Replacement fuse, for INTERBUS-ST modules



# I/O module - IB ST 24 BAO 8/U

2721044

<https://www.phoenixcontact.com/us/products/2721044>



## Insertion bridge

Insertion bridge - EB 84 IB ST BU - 2836269

<https://www.phoenixcontact.com/us/products/2836269>

Insertion bridges, divisible, isolated comb spine, color blue, 84-pos.



---

## Insertion bridge

Insertion bridge - EB 84 IB ST RD - 2836272

<https://www.phoenixcontact.com/us/products/2836272>

Insertion bridges, divisible, isolated comb spine, color red, 84-pos.



---

Phoenix Contact 2022 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)