

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0622018641

Status:

Active

Overview:

Application Tooling

Description:

Daughter Card Module Installation Press-In Tool

Documents:

RoHS Certificate of Compliance (PDF)


General	
Product Family	Application Tooling
Series	207123
Comments	See Tooling Specification (PDF) Above, Press-In Tool
Function	Insertion
Geographic Area	Global
Level of Automation	Manual
More Detailed Tech Information	applicationtooling@molex.com
Overview	Application Tooling
Product Name	PremiumGrade
Tool Type	Press-Fit Insertion Tool
UPC	800756930633
Warranty Disclaimer	CAUTION: Molex tooling crimp specifications are valid only when used with Molex terminals and tooling manufactured by Molex and sold by Molex or authorized distributors ("Molex Tooling"). When using tooling other than Molex Tooling with Molex specific connector systems listed in our ATS documents, the Molex tooling qualification does not apply and the responsibility for full qualification of the connector system is that of the customer. Molex accepts no liability for connector performance or tooling support where tooling other than Molex Tooling is used or where Molex Tooling is modified.

Material Info

Reference - Drawing Numbers

Application Tooling Documents

ATS-622018641, TM-622018799



Series image - Reference only

EU ELV	
Not Relevant	
EU RoHS	China RoHS
Not Reviewed	
REACH SVHC	
Not Reviewed	
Halogen-Free	
Status	
Not Relevant	
For more information, please visit Contact US	
China ROHS	Not Relevant
ELV	Not Relevant
RoHS Phthalates	Not Reviewed

Search Parts in this Series

207123 Series

Use With

Impact Daughtercard Signal Module, 76160 Series

Application Tooling Description	FAQ Product #
Impact 85 Ohm Plus 4 Pair, Right-Angle Daughtercard, Unguided, 10 Columns, 120 Circuits, Plated Through Hole Dimension 0.39mm, Lead Free	1703401020
Impact 85 Ohm Plus 4 Pair, Right-Angle Daughtercard, Left Guided, 10 Columns, 120 Circuits, Plated Through Hole Dimension 0.46mm, Lead Free	1703403010

Impact 85 Ohm Plus 1703403020
4 Pair, Right-Angle
Daughtercard, Left
Guided, 10 Columns,
120 Circuits, Plated
Through Hole
Dimension 0.39mm,
Lead Free

Impact 85 Ohm Plus 1703405010
4 Pair, Right-Angle
Daughtercard, Right
Guided, 10 Columns,
120 Circuits, Plated
Through Hole
Dimension 0.46mm,
Lead Free

Impact 85 Ohm Plus 1703405020
4 Pair, Right-Angle
Daughtercard, Right
Guided, 10 Columns,
120 Circuits, Plated
Through Hole
Dimension 0.39mm,
Lead Free

Impact 100 Ohm 761601010
4 Pair Right-Angle
Daughtercard
Receptacle,
Unguided, 10
Columns, 120
Circuits, Plated
Through Hole
Dimension 0.46mm,
Lead-Free

Impact 100 Ohm 761601020
4 Pair Right-Angle
Daughtercard
Receptacle,
Unguided, 10
Columns, 120
Circuits, Plated
Through Hole
Dimension 0.39mm,
Lead-Free

Impact 100 Ohm 761603010
4 Pair Right-Angle
Daughtercard
Receptacle, Left
Guided, 10 Columns,
120 Circuits, Plated
Through Hole
Dimension 0.46mm,
Lead-Free

Impact 100 Ohm 761603020
4 Pair Right-Angle
Daughtercard
Receptacle, Left
Guided, 10 Columns,
120 Circuits, Plated
Through Hole
Dimension 0.39mm,
Lead-Free

Impact 100 Ohm 761603120
4 Pair Right-Angle
Daughtercard

Receptacle, Left Guided,10 Columns, 120 Circuits, Plated Through Hole Dimension 0.39mm, Polarizing Key Position A, Lead- Free Impact 100 Ohm 4 Pair Right-Angle Daughtercard	<u>761605010</u>
Receptacle, Right Guided, 10 Columns, 120 Circuits, Plated Through Hole Dimension 0.46mm, Lead-Free Impact 100 Ohm 4 Pair Right-Angle Daughtercard	<u>761605020</u>
Receptacle, Right Guided, 10 Columns, 120 Circuits, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm 4 Pair Right-Angle Daughtercard	<u>761605120</u>
Receptacle, Right Guided, 10 Columns, 120 Circuits, Plated Through Hole Dimension 0.39mm, Polarizing Key Position A, Lead- Free Impact 100 Ohm 4 Pair Right-Angle Daughtercard	<u>761605220</u>
Receptacle, Right Guided, 10 Columns, 120 Circuits, Plated Through Hole Dimension 0.39mm, Polarizing Key Position B, Lead Free Impact 100 Ohm 4 Pair Right-Angle Daughtercard	<u>761605310</u>
Receptacle, Right Guided, 10 Columns, 120 Circuits, Plated Through Hole Dimension 0.46mm, Polarizing Key Position C, Lead Free Impact 100 Ohm 4 Pair Right-Angle Daughtercard	<u>761605320</u>
Receptacle, Right Guided, 10 Columns, 120 Circuits, Plated	

	Through Hole Dimension 0.39mm, Polarizing Key Position C, Lead Free Impact 100 Ohm <u>765001104</u> 4 Pair RAM Right- Angle Header, Unguided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated
	Through Hole Dimension 0.46mm, Lead Free Impact 100 Ohm <u>765001105</u> 4 Pair RAM Right- Angle Header, Unguided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated
	Through Hole Dimension 0.46mm, Lead Free Impact 100 Ohm <u>765001107</u> 4 Pair RAM Right- Angle Header, Unguided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated
	Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765001108</u> 4 Pair RAM Right- Angle Header, Unguided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated
	Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765001115</u> 4 Pair RAM Right- Angle Header, Unguided, Left Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated
	Through Hole Dimension 0.46mm, Lead Free Impact 100 Ohm <u>765001117</u> 4 Pair RAM Right- Angle Header, Unguided, Left Endwall, 10

	Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765001118</u> 4 Pair RAM Right- Angle Header, Unguided, Left Endwall, 10
	Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765001127</u> 4 Pair RAM Right- Angle Header, Unguided, Dual Endwall, 10
	Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765001128</u> 4 Pair RAM Right- Angle Header, Unguided, Dual Endwall, 10
	Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765001135</u> 4 Pair RAM Right- Angle Header, Unguided, Right Endwall, 10
	Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead Free Impact 100 Ohm <u>765001137</u> 4 Pair RAM Right- Angle Header, Unguided, Right Endwall, 10
	Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead Free Impact 100 Ohm <u>765001138</u> 4 Pair RAM Right- Angle Header, Unguided, Right

	Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765003104</u> 4 Pair RAM Right- Angle Header, Left Guided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.46mm, Lead Free Impact 100 Ohm <u>765003105</u> 4 Pair RAM Right- Angle Header, Left Guided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead Free Impact 100 Ohm <u>765003107</u> 4 Pair RAM Right- Angle Header, Left Guided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765003108</u> 4 Pair RAM Right- Angle Header, Left Guided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765005104</u> 4 Pair RAM Right- Angle Header, Right Guided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.46mm, Lead Free Impact 100 Ohm <u>765005105</u> 4 Pair RAM Right- Angle Header,
--	--

	Right Guided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead Free Impact 100 Ohm 765005107 4 Pair RAM Right- Angle Header, Right Guided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm 765005108 4 Pair RAM Right- Angle Header, Right Guided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm 765007107 4 Pair RAM Right- Angle Header, Left Guided, Right Endwall, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm 765009108 4 Pair RAM Right- Angle Header, Right Guided, Left Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm 768501010 4 Pair Right- Angle Orthogonal Daughtercard, Unguided, 10 Columns, 120 Circuits, Plated Through Hole Dimension 0.46mm, Lead-Free Impact 100 Ohm 768501020 4 Pair Right- Angle Orthogonal Daughtercard,	
--	--	--

Unguided, 10
Columns, 120
Circuits, Plated
Through Hole
Dimension 0.39mm,
Lead-Free
Impact 100 Ohm 768503010
4 Pair Right-
Angle Orthogonal
Daughtercard, Left
Guide, 10 Columns,
120 Circuits, Plated
Through Hole
Dimension 0.46mm,
Lead-Free
Impact 100 Ohm 768503020
4 Pair Right-
Angle Orthogonal
Daughtercard, Left
Guide, 10 Columns,
120 Circuits, Plated
Through Hole
Dimension 0.39mm,
Lead-Free
Impact 100 Ohm 768505010
4 Pair Right-
Angle Orthogonal
Daughtercard, Right
Guide, 10 Columns,
120 Circuits, Plated
Through Hole
Dimension 0.46mm,
Lead-Free
Impact 100 Ohm 768505020
4 Pair Right-
Angle Orthogonal
Daughtercard, Right
Guide, 10 Columns,
120 Circuits, Plated
Through Hole
Dimension 0.39mm,
Lead-Free