



NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. RATING: 12VDC, 50mA
- ▲ 5. OPERATING FORCE: 250 \pm 50 gf
6. TRAVEL: 0.25 +0.2/-0.1 mm
7. CONTACT RESISTANCE: 50 MILLI OHMS MAX. (INITIAL)
8. MECHANICAL/ELECTRICAL LIFE 100,000 CYCLES MIN.
- ▲ 9. CONTACT MATERIAL: SILVER
10. ▲ DENOTES CRITICAL PARAMETER
11. OPERATING TEMP: -40°C TO 85°C

D	24551	REMOVE STEP IN HOUSING, CHANGE TEMP	10/29/20	JM
C	22850	ADD 3.7 TERMINAL DIM.	5/26/17	MW
B	18677	LEG TOLERANCE WAS +/- 0.1	10/9/9	BLR
REV	PCR NO	DESCRIPTION	DATE	BY



TITLE TL1105WF250Q				
SCALE	DATE	DR	DWG	REV
4:1	10/9/2009	BLR	P021219	D

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED