






NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. RATING: 12VDC, 50mA
- ▲ 5. OPERATING FORCE: 160 $\pm$ 50 gf
6. TRAVEL: 0.25 +0.2/-0.1 mm
7. CONTACT RESISTANCE: 50 MILLI OHMS MAX. (INITIAL)
8. MECHANICAL/ELECTRICAL LIFE 100,000 CYCLES MIN.
- ▲ 9. CONTACT MATERIAL: SILVER
10. ▲ DENOTES CRITICAL PARAMETER
- ▲ 11. HOUSING & ACTUATOR: TO MEET UL-94V0 STANDARD
- ▲ 12. ACTUATOR COLOR: WHITE (NATURAL NYLON)
13. OPERATING TEMP: -40°C TO 85°C



D	24550	REMOVE STEP IN HOUSING, CHANGE TEMP	10/19/20	JM
C	21583	CHANGE TITLE TO MATCH QAD	9/17/14	EBP
B	18128	ONE TOLERANCE WAS +/- 0.1	6/9/08	BLR
A	15932	RELEASED	4/4/06	PH
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY
TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED



E-SWITCH®

TITLE TL1105MF160Q94V0WHTACT

SCALE
4:1DATE
4/4/2006DR
PHDWG
P020237REV
D