



### SPECIFICATION

1. Rating : DC 30V 1.0A;
2. Contact resistance:  $\leq 0.03 \Omega$ ;
3. Insulation resistance:  $\geq 100M \Omega$  (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-20N;
6. life test: 5,000 cycles.

PIN	$\phi 2.0$	$\phi 2.5$
APPD.		✓

### 包装要求:

1. 每500PCS装1PE袋, 每箱入数可视订单量大小调整.
2. 每袋贴上一张合格标签、ROHS标签, 外箱贴上产品标签

6	COVER	1	PBT UL 94V-0	BLACK
5	HOUSING	1	PBT UL 94V-0	BLACK
4	PIN	1	C3604	NI PLATED
3	TIP SPRING	1	SHELL	Sn PLATED
2	TERMINAL	1	C2680	Sn PLATED
1	SHUNT SPRING	1	C2680	Sn PLATED
LTR	PART NAME	QTY	MATERIAL	FINISH

### TOLERANCE TABLE

.0	$\pm 0.20$
.00	$\pm 0.10$
.000	$\pm 0.05$

APPROVED:	DATE:	Ckmtw 深圳市灿科盟实业有限公司 CHANKEMENG INDUSTRYCO., LTD			
CHECKED:	DATE:	TITLE: DC JACK 电源座 (DC-00050)			
DRAWN: luli-Liu	DATE: 2015-04-25	CLIENT P/N	C840489		
		UNIT	mm	SCALE	free
		FILE NO.	Z-DC00R02P-2500	REV.	A ZZDZ