

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
APPLICATION STANDARD									
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO +85 °C			STORAGE TEMPERATURE RANGE	--- °C TO --- °C			
	VOLTAGE	200V AC			OPERATING HUMIDITY RANGE	--- % TO --- %			
	CURRENT	2 A			APPLICABLE CABLE	AWG#26~36			
SPECIFICATIONS									
ITEM	TEST METHOD			REQUIREMENT			QT	AT	
CONSTRUCTION									
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT. ACCORDING TO DRAWING						X	X	
MARKING	CONFIRMED VISUALLY						X	X	
ELECTRICAL CHARACTERISTICS									
INSULATION RESISTANCE	500 V DC			1000 MΩ MIN.			X	—	
VOLTAGE PROOF	650 V AC FOR 1 min.			NO FLASHOVER OR BREAKDOWN			X	—	
ENVIRONMENTAL CHARACTERISTICS									
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90~95 %, 96 h.			1) INSULATION RESISTANCE: 1000 MΩ MIN. 2) NO DAMAGE, CRACK AND LOOSENESS OF PART.			X	—	
RAPID CHAGE OF TEMPERTURE	TEMPERTURE-55→15~35→ 85→15~35°C TIME 30→10~15→ 30 → 10~15 min. UNDER 5 CYCLES.			NO DAMAGE, CRACK AND LOOSENESS OF PART.			X	—	
REMARKS				DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED	
UNLESS OTHERWISE SPECIFIED, REFER TO MIL-STD-1344				M.ISHIZUKA 99.09.25	H. Okawa 99.09.25	J. Yamaguchi 99.09.25	J. Yamaguchi 99.09.25		
NOTE	QT: QUALIFICATION TEST	AT: ASSURANCE TEST	O: APPLICABLE TEST						
TO	PCK								
HRS HIROSE ELECTRIC CO.,LTD.		SPECIFICATION SHEET			A3B - 24D - 2C				
CODE NO.(OLD)		DRAWING NO.		CODE NO.					1
CL		ELC4 - 021400		CL 621 - 0313 - 6					1
FORM NO. 231-1									