TRIPP-LITE

Computer Power Cord, C19 to NEMA 5-15P -Heavy-Duty, 15A, 125V, 14 AWG, 8 ft. (2.43 m), Black

MODEL NUMBER: P034-008



C19 to 5-15P adapter connects devices with C20/NEMA 5-15R power connectors or extends your existing power connection by 8 ft.

Features

Heavy-Duty Computer Power Cable for Devices That Require a Heavy-Gauge ConnectionThis C19 to 5-15P computer power cord features 14 AWG wire suitable for high power connections, making it a reliable solution for large server applications that require a higher-rated, heavier-gauge cable. It can be used to connect a computer, server, monitor or drive to a UPS system or PDU or replace or upgrade the standard power cord provided by the device's manufacturer. The 8-ft. (2.43 m) length allows you great flexibility in placing equipment with respect to the power outlet.

Specifications

OVERVIEW	
UPC Code	037332188717
Device Compatibility	Computer; Monitor/HDTV; Server; UPS; PDU
Country/Region	North America
INPUT	
Maximum Input Amps	15
Voltage Compatibility (VAC)	125
PHYSICAL	
Plug Color	Black
Cable Jacket Color	Black

Highlights

- Recommended for powering computers, servers and other network devices
- 8-ft. (2.43 m) length allows great flexibility in placing devices in relationship to AC outlet
- Heavy-duty computer power cord replaces or upgrades cord provided by manufacturer
- Thick 14 AWG wire gauge manages high power levels required for larger equipment

Applications

- Connect devices like computers, servers and monitors to a PDU up to 8-ft. (2.43 m) away in your data center
- Extend an existing power connection up to 8-ft. (2.43 m) to more easily place a device or reach a power source
- Update or replace the standard power cord provided by a device's original manufacturer

Package Includes

• P034-008 Computer Power Cable, C19 to 5-15P, 8-ft. (2.43 m), Black

TRIPP-LITE

PVC	
VW-1	
SJT	
9.3mm	
3	
14	
2.08	
8	
2.44	
8.85 x 12.80 x 0.50	
22.48 x 32.51 x 1.27	
0.95	
0.43	
14 F TO 140 F (-10 C TO 60 C)	
14 F TO 140 F (-10 C TO 60 C)	
35% to 85% RH, Non-Condensing	
35% to 85% RH, Non-Condensing	
Storage Humidity Range 35% to 85% RH, Non-Condensing CONNECTIONS	
NEMA 5-15P	
IEC-320-C19	
FEATURES & SPECIFICATIONS	
No	
STANDARDS & COMPLIANCE Product Certifications cUL Listed; UL Listed	
cUL Listed; UL Listed	
RoHS	
WARRANTY & SUPPORT	



1000 Eaton Boulevard Cleveland, OH 44122 United States



© 2022 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.