



- NOTES:
1. MATERIAL: PA66 GF 30%
  2. ALLOWABLE FLASH 0.08 UNLESS OTHERWISE SPECIFIED.
  3. PACKAGING AS PER PK-36804-001
  4. USE WITH 36792/36807 SERIES

<b>PART# REPLACEMENT</b> EC NO: I2015-0163 CHIKO: APPR:KPRASAD	DESCRIPTION 2015/05/25	<b>QUALITY SYMBOLS</b> $\nabla=0$ $\nabla=0$ $\nabla=0$		<b>GENERAL TOLERANCES (UNLESS SPECIFIED)</b>		<b>DIMENSION STYLE</b> <b>MM ONLY</b>		<b>SCALE</b> <b>10:1</b>	<b>DESIGN UNITS</b> <b>METRIC</b>	<b>THIRD ANGLE PROJECTION</b>
		4 PLACES ± --- ± ---	mm INCH	DRAWN BY MRAMAKRISHNA	DATE 2012/07/05	<b>TITLE</b> MX 120G CAVITY PLUG FOR RECEPTACLE				
		3 PLACES ± --- ± ---	2 PLACES ± 0.13 ± ---	CHECKED BY	DATE					
		1 PLACE ± 0.25 ± ---	0 PLACE ± --- ± ---	APPROVED BY KPRASAD	DATE 2013/09/30				<b>MATERIAL NO.</b> 368040001	<b>DOCUMENT NO.</b> SD-36804-001
ANGULAR ± --- °				DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE A2		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		