



SPECIFICATIONS:

1. MATERIAL:
 - (A). BODY: PA66
 - (B). PIN: BRASS
2. WIRE RANGE: N/A
3. ELECTRICAL RATING: 300V, 15A.
4. WIRE STRIP LENGTH: N/A.
5. OPERATING TEMPERATURE: -40°C to +105°C.
6. MAX TORQUE: N/A.
7. INSULATION RESISTANCE: DC 500V, 500M.
8. DIELECTRIC WITHSTAND: AC 2500V FOR 1 MINUTE.
9. BREAKDOWN VOLTAGE : 4000V.
10. $A = (N \times P)$
11. $B = (N - 1) \times P$
12. P (PITCH) = 5.08MM (.200").
13. N = NUMBER OF POSITIONS AVAILABLE 2 THROUGH 24.
14. DIMS SHOWN ARE FOR REFERENCE ONLY.

TOLERANCES			
MM	TOL	INCH	TOL
0-6	±0.25	0-.24	±.010
>6-30	±0.40	.24-1.18	±.016
>30-120	±0.50	1.18-4.76	±.020
>120	±0.80	>4.76	±.031

SYMBOLS DIMENSION UNITS: MM/INCH SCALE: 4:1 GENERAL TOLERANCES (UNLESS SPECIFIED): 4 PLACES ± --- ± --- 3 PLACES ± --- ± SEE CHART 2 PLACES ± SEE CHART ± SEE CHART 1 PLACE ± SEE CHART ± --- 0 PLACES ± --- ± --- ANGULAR TOL ± --- DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION CURRENT REV DESC: MIGRATION TO ECTR/NX EC NO: 623382 DRWN: ABENJAMINLW 2019/07/18 CHK'D: DACHAMMER 2019/09/03 APPR: JFMURPHY 2019/09/26 INITIAL REVISION: DRWN: LROTHAUS 2006/01/09 APPR: JPAWLICK 2006/01/10		moLEX 5.08MM, EURO HEADER, VERTICAL, OPEN END PRODUCT CUSTOMER DRAWING DOCUMENT NUMBER: SD-39531-003 DOC TYPE: PSD DOC PART: 001 REVISION: A2	
DOCUMENT STATUS: P1 RELEASE DATE: 2019/09/26 15:47:07	THIRD ANGLE PROJECTION DRAWING: B-SIZE SERIES: 39531	MATERIAL NUMBER: SEE SHEET-2 CUSTOMER: GENERAL MARKET	SHEET NUMBER: 1 OF 2		

	10	9	8	7	6	5	4	3	2	1								
F	DESCRIPTION		MATERIAL NUMBERS											DIMENSIONAL INFORMATION				
			BLACK					GREEN										
			100% TIN			30 u" GOLD		100% TIN			30 u" GOLD							
CIRCUIT SIZE	PRINTING OPTIONS			PRINTING OPTIONS			PRINTING OPTIONS			PRINTING OPTIONS			DIM. "A"		DIM. "B"			
	None	10AV	11AV	None	10AV	11AV	None	10AV	11AV	None	10AV	11AV	None	10AV	11AV	mm	inch	mm
E	5.08 MM, EURO HEADER, VERTICAL, OPEN END	2	395310002	395310302	395310402	395310502	395310802	395310902	395315002	395315302	395315402	395315502	395315802	395315902	10.16	.400	5.08	.200
E	5.08 MM, EURO HEADER, VERTICAL, OPEN END	3	395310003	395310303	395310403	395310503	395310803	395310903	395315003	395315303	395315403	395315503	395315803	395315903	15.24	.600	10.16	.400
E	5.08 MM, EURO HEADER, VERTICAL, OPEN END	4	395310004	395310304	395310404	395310504	395310804	395310904	395315004	395315304	395315404	395315504	395315804	395315904	20.32	.800	15.24	.600
E	5.08 MM, EURO HEADER, VERTICAL, OPEN END	5	395310005	395310305	395310405	395310505	395310805	395310905	395315005	395315305	395315405	395315505	395315805	395315905	25.40	1.000	20.32	.800
E	5.08 MM, EURO HEADER, VERTICAL, OPEN END	6	395310006	395310306	395310406	395310506	395310806	395310906	395315006	395315306	395315406	395315506	395315806	395315906	30.48	1.200	25.40	1.000
E	5.08 MM, EURO HEADER, VERTICAL, OPEN END	7	395310007	395310307	395310407	395310507	395310807	395310907	395315007	395315307	395315407	395315507	395315807	395315907	35.56	1.400	30.48	1.200
E	5.08 MM, EURO HEADER, VERTICAL, OPEN END	8	395310008	395310308	395310408	395310508	395310808	395310908	395315008	395315308	395315408	395315508	395315808	395315908	40.64	1.600	35.56	1.400
E	5.08 MM, EURO HEADER, VERTICAL, OPEN END	9	395310009	395310309	395310409	395310509	395310809	395310909	395315009	395315309	395315409	395315509	395315809	395315909	45.72	1.800	40.64	1.600
E	5.08 MM, EURO HEADER, VERTICAL, OPEN END	10	395310010	395310310	395310410	395310510	395310810	395310910	395315010	395315310	395315410	395315510	395315810	395315910	50.80	2.000	45.72	1.800
D	5.08 MM, EURO HEADER, VERTICAL, OPEN END	11	395310011	395310311	395310411	395310511	395310811	395310911	395315011	395315311	395315411	395315511	395315811	395315911	55.88	2.200	50.80	2.000
D	5.08 MM, EURO HEADER, VERTICAL, OPEN END	12	395310012	395310312	395310412	395310512	395310812	395310912	395315012	395315312	395315412	395315512	395315812	395315912	60.96	2.400	55.88	2.200
D	5.08 MM, EURO HEADER, VERTICAL, OPEN END	13	395310013	395310313	395310413	395310513	395310813	395310913	395315013	395315313	395315413	395315513	395315813	395315913	66.04	2.600	60.96	2.400
D	5.08 MM, EURO HEADER, VERTICAL, OPEN END	14	395310014	395310314	395310414	395310514	395310814	395310914	395315014	395315314	395315414	395315514	395315814	395315914	71.12	2.800	66.04	2.600
D	5.08 MM, EURO HEADER, VERTICAL, OPEN END	15	395310015	395310315	395310415	395310515	395310815	395310915	395315015	395315315	395315415	395315515	395315815	395315915	76.20	3.000	71.12	2.800
D	5.08 MM, EURO HEADER, VERTICAL, OPEN END	16	395310016	395310316	395310416	395310516	395310816	395310916	395315016	395315316	395315416	395315516	395315816	395315916	81.28	3.200	76.20	3.000
D	5.08 MM, EURO HEADER, VERTICAL, OPEN END	17	395310017	395310317	395310417	395310517	395310817	395310917	395315017	395315317	395315417	395315517	395315817	395315917	86.36	3.400	81.28	3.200
D	5.08 MM, EURO HEADER, VERTICAL, OPEN END	18	395310018	395310318	395310418	395310518	395310818	395310918	395315018	395315318	395315418	395315518	395315818	395315918	91.44	3.600	86.36	3.400
C	5.08 MM, EURO HEADER, VERTICAL, OPEN END	19	395310019	395310319	395310419	395310519	395310819	395310919	395315019	395315319	395315419	395315519	395315819	395315919	96.52	3.800	91.44	3.600
C	5.08 MM, EURO HEADER, VERTICAL, OPEN END	20	395310020	395310320	395310420	395310520	395310820	395310920	395315020	395315320	395315420	395315520	395315820	395315920	101.60	4.000	96.52	3.800
C	5.08 MM, EURO HEADER, VERTICAL, OPEN END	21	395310021	395310321	395310421	395310521	395310821	395310921	395315021	395315321	395315421	395315521	395315821	395315921	106.68	4.200	101.60	4.000
C	5.08 MM, EURO HEADER, VERTICAL, OPEN END	22	395310022	395310322	395310422	395310522	395310822	395310922	395315022	395315322	395315422	395315522	395315822	395315922	111.76	4.400	106.68	4.200
C	5.08 MM, EURO HEADER, VERTICAL, OPEN END	23	395310023	395310323	395310423	395310523	395310823	395310923	395315023	395315323	395315423	395315523	395315823	395315923	116.84	4.600	111.76	4.400
C	5.08 MM, EURO HEADER, VERTICAL, OPEN END	24	395310024	395310324	395310424	395310524	395310824	395310924	395315024	395315324	395315424	395315524	395315824	395315924	121.92	4.800	116.84	4.600
B																		
B																		
A																		

TOLERANCES			
MM	TOL	INCH	TOL
0-6	±0.25	0-.24	±.010
>6-30	±0.40	.24-1.18	±.016
>30-120	±0.50	1.18-4.76	±.020
>120	±0.80	>4.76	±.031

SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																	
	= 0 = 0 = 0 = 0 = 0 = 0 = 0 = 0 = 0	DIMENSION UNITS MM/INCH	SCALE 4:1	CURRENT REV DESC: MIGRATION TO ECTR/NX														
GENERAL TOLERANCES (UNLESS SPECIFIED)			EC NO: 623382			DRWN: ABENJAMINLW 2019/07/18			CHK'D: DACHAMMER 2019/09/03			APPR: JFMURPHY 2019/09/26			INITIAL REVISION:			
4 PLACES ± --- ± ---			DRWN: LROTHAUS 2006/01/09			APPR: JPAWLICK 2006/01/10			MATERIAL NUMBER			CUSTOMER			SHEET NUMBER			
3 PLACES ± --- ± SEE CHART			SD-39531-003			GENERAL MARKET			SEE TABLE			2 OF 2						
2 PLACES ± SEE CHART ± SEE CHART																		
1 PLACE ± SEE CHART ± ---																		
0 PLACES ± --- ± ---																		
ANGULAR TOL ± ---																		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			THIRD ANGLE PROJECTION			DRAWING			SERIES									
			B-SIZE			39531												

DOCUMENT STATUS P1 RELEASE DATE 2019/09/26 15:47:07

10 9 8 7 6 5 4 3 2 1