



PCB LAYOUT

Specifications:

规格:

Voltage rating: 150V AC/DC
 额定电压: 150V AC/DC
 Current rating: 1A AC/DC
 额定电流: 1A AC/DC
 Withstanding voltage: 500V AC/minute
 耐受电压: 500V AC/分钟
 Temperature range: -40°C~+85°C
 温度范围: -40°C~+85°C
 Insulation resistance: ≥500MΩ min
 绝缘电阻: ≥500MΩ Min
 Contact resistance: ≤30mΩ Max
 接触电阻: ≤30mΩ Max

X9812 W V S - 2xXX - 9T V01
 ① ② ③ ④ ⑤ ⑥ ⑦

1. Series No
2. Category: W-Wafer
3. Welding Board Angle: V-Stright 180°
4. Welding Way: S-SMT
5. Row No. Pin No: XX-2x05~2x25P
6. Material: 9T-PA9T UL 94V-0 Natural
CAP: PA9T UL 94V-0 Natural
7. Plating: V01-Gold Flash

Poles	Dimensions(mm)		
	A	B	C
2x05	5.00	12.50	6.10
2x10	11.25	18.75	12.35
2x15	17.50	25.00	18.60
2x20	23.75	31.25	24.85
2x25	30.00	37.50	31.10

X9812WVS-2xXX-9TV01	PA9T	Brass	X9812H
PART NO	Material	Material(Pin)	Suitable XKB Housing

DSND	SCALE: N/A	MODEL TYPE: 1.25mm Crimp Style Connector
DWN	VIEW:	PART NO.: X9812WVS-2xXX-9TV01
CHKD	UNIT: mm/in	DWG NO.: X-X9812WVS-2xXX-9TV01
APPD	SIZE: A4	WEIGHT SHEET REVISION
		1/1 A0



XKB INDUSTRIAL PRECISION CO., LIMITED

ANGLAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5
UNSPECIFIED TOLERANCES	

广东星坤科技股份有限公司

DATE	日期
MARK	文件工程章

REVISIONS