NCP4687

Linear Voltage Regulator, LDO, High PSRR, 500 mA

The NCP4687 is a CMOS 500 mA LDO linear voltage regulator with high output voltage accuracy which features a high ripple rejection, low supply current with low dropout and chip enable with built−in low $R_{DS(on)}$ NMOS transistor for fast output capacitor discharging as option. The device is composed of the voltage reference unit, error amplifier, resistor divider for output voltage sensing or precise output voltage setting. The current limit and thermal shutdown makes the device very suitable for industrial applications and portable communication equipments.

Features

- Operating Input Voltage Range: 2.5 V to 5.25 V
- Output Voltage Range: 0.7 to 3.6 V (available in 0.1 V steps)
- ±0.8% Output Voltage Accuracy @ V_{out} > 1.8 V
- Output noise : 40 μV_{rms}
- Line Regulation: 0.02%/V
- Current Limit Circuit
- High PSRR: 75 dB at 1 kHz, 70 dB at 10 kHz
- Thermal Shutdown
- Available in SOT−23−5, SOT−89−5 and uDFN 1.2 x 1.2 mm Packages
- These Devices are Pb−Free and are RoHS Compliant

Typical Applications

- Home Appliances, Industrial Equipment
- DVB−T and DVB−S Receivers
- Car Audio Equipment, Navigation Systems
- Notebook Adaptors, LCD TVs, Cordless Phones and Private LAN Systems



Figure 1. Typical Application Schematic

ON Semiconductor™

http://onsemi.com

MARKING DIAGRAMS

SOT89−5
CASE 528AB



XDFN6
CASE 711AH



SOT−23−5
CASE 1212



XX, XXX = Specific Device Code
ZZ = Lot Code
MM = Date Code

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 15 of this data sheet.

© Semiconductor Components Industries, LLC, 2014



Figure 2. Simplified Schematic Block Diagram

PIN FUNCTION DESCRIPTION

Pin No. SOT−23−5	Pin No. SOT−89−5	Pin No. DFN1212	Pin Name	Description
1	4	6	VIN	Input pin
2	2	3	GND	Ground pin
3	3	4	CE	Chip enable pin (“H” active)
4	1	2	SENSE	Output Voltage Sensing
5	5	1	VOUT	Output pin
		5	NC	Non Connected
		*EP	EP	Exposed Pad (leave floating or connect to GND)

ABSOLUTE MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Input Voltage	V_{IN}	0 − 6	V
Output Voltage	V_{OUT}	−0.3 to V_{IN} − 0.3	V
Chip Enable Input	V_{CE}	−0.3 − 6	V
Power Dissipation SOT−23−5	P_D	420	mW
Power Dissipation uDFN 1.2 x 1.2 mm		600	
Power Dissipation SOT−89−5		900	
Junction Temperature	T_J	−40 to 150	°C
Storage Temperature	T_{STG}	−55 to 125	°C
ESD Capability, Human Body Model (Note 1)	ESD_{HBM}	2000	V
ESD Capability, Machine Model (Note 1)	ESD_{MM}	200	V

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. This device series incorporates ESD protection and is tested by the following methods:
   ESD Human Body Model tested per AEC−Q100−002 (EIA/JESD22−A114)
   ESD Machine Model tested per AEC−Q100−003 (EIA/JESD22−A115)
   Latchup Current Maximum Rating tested per JEDEC standard: JESD78

THERMAL CHARACTERISTICS

Rating	Symbol	Value	Unit
Thermal Characteristics, SOT−23−5 Thermal Resistance, Junction−to−Air	$R_{\theta JA}$	238	°C/W
Thermal Characteristics, uDFN 1.2x1.2 Thermal Resistance, Junction−to−Air	$R_{\theta JA}$	167	°C/W
Thermal Characteristics, SOT−89−5 Thermal Resistance, Junction−to−Air	$R_{\theta JA}$	111	°C/W

ELECTRICAL CHARACTERISTICS −40°C ≤ T_A ≤ 85°C; C_{IN} = C_{OUT} = 1.0 μF, unless otherwise noted. Typical values are at T_A = +25°C.

Parameter	Test Conditions		Symbol	Min	Typ	Max	Unit
Operating Input Voltage	V_{OUT} ≤ 1.5 V		V_{IN}	2.5		5.25	V
	V_{OUT} > 1.5 V			V_{OUT} + 1		5.25	
Output Voltage	Ta = 25°C, V_{OUT} > 1.8 V		V_{OUT}	x0.992		x1.008	V
	−40°C < Ta < 85°C, V_{OUT} > 1.8 V			x0.985		x1.015	V
	Ta = 25°C, V_{OUT} ≤ 1.8 V			−18		+18	mV
	−40°C < Ta < 85°C, V_{OUT} ≤ 1.8 V			−55		+55	mV
Output Voltage Temp. Coefficient	−40°C < Ta < 85°C, V_{OUT} > 1.8 V				±30		ppm/°C
	−40°C < Ta < 85°C, V_{OUT} ≤ 1.8 V				±100		
Load Regulation	1 mA < I_{OUT} ≤ 500 mA		$Load_{Reg}$		1	20	mV
Line Regulation	Set V_{OUT} + 0.5 V < V_{IN} < 5.25 V		$Line_{Reg}$		0.02	0.1	%/V
Dropout Voltage	I_{OUT} = 500 mA	0.7 V ≤ V_{OUT} < 0.8 V	V_{DO}		0.58	0.88	V
		0.8 V ≤ V_{OUT} < 0.9 V			0.52	0.80	
		0.9 V ≤ V_{OUT} < 1.0 V			0.45	0.70	
		1.0 V ≤ V_{OUT} < 1.2 V			0.42	0.64	
		1.2 V ≤ V_{OUT} < 1.4 V			0.35	0.53	
		1.4 V ≤ V_{OUT} < 1.8 V			0.31	0.48	
		1.8 V ≤ V_{OUT} < 2.1 V			0.27	0.41	
		2.1 V ≤ V_{OUT} < 2.5 V			0.25	0.38	
		2.5 V ≤ V_{OUT} < 3.0 V			0.23	0.34	
		3.0 V ≤ V_{OUT} < 3.6 V			0.22	0.32	
Output Current			I_{OUT}	500			mA
Short Current Limit	V_{OUT} = 0 V		I_{SC}		50		mA
Quiescent Current	I_{OUT} = 0 mA	V_{OUT} > 1.5 V	I_Q		80	115	μA
		V_{OUT} ≤ 1.5 V			75		
Standby Current	V_{IN} = $V_{IN\ max}$, V_{CE} = 0 V		I_{STB}		0.1	1.0	μA
CE Pin Pull−Down Current			I_{PD}		0.3	0.6	μA
CE Pin Threshold Voltage	CE Input Voltage “H”		V_{CEH}	1.0		V_{IN}	V
	CE Input Voltage “L”		V_{CEL}			0.4	
Power Supply Rejection Ratio	V_{OUT} ≤ 2.0 V @ V_{IN} = 3.0 V, V_{OUT} > 2.0 V @ V_{IN} = = Set V_{OUT} + 1.0 V, ΔV_{IN_PK-PK} = 0.2 V, I_{OUT} = 30 mA	f = 1 kHz	PSRR		75		dB
		f = 10 kHz			70		
Output Noise Voltage	I_{OUT} = 30 mA , f = 10 Hz to 100 kHz, V_{OUT} > 1.8 V		V_{NOISE}		20 x V_{OUT}		μV_{rms}
	I_{OUT} = 30 mA, f = 10 Hz to 100 kHz, V_{OUT} ≤ 1.8 V				40 x V_{OUT}		
Thermal Shutdown / Hysteresis					165/65		°C
Auto−discharge N−MOS Resistance	V_{IN} = 4.0 V, V_{CE} = 0.0 V (Note 2)		$R_{DS(on)}$		60		Ω

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

2.

TYPICAL CHARACTERISTICS



Figure 3. Output Voltage vs. Output Current 0.7 V Version



Figure 4. Output Voltage vs. Output Current 2.5 V Version



Figure 5. Output Voltage vs. Output Current 3.6 V Version



Figure 6. Output Voltage vs. Input Voltage 0.7 V Version



Figure 7. Output Voltage vs. Input Voltage 2.5 V Version



Figure 8. Output Voltage vs. Input Voltage 3.6 V Version

TYPICAL CHARACTERISTICS



Figure 9. Output Voltage vs. Temperature, 0.7 V Version



Figure 10. Output Voltage vs. Temperature, 2.5 V Version



Figure 11. Output Voltage vs. Temperature, 3.6 V Version



Figure 12. Dropout Voltage vs. Output Current, 0.7 V Version



Figure 13. Dropout Voltage vs. Output Current, 2.5 V Version



Figure 14. Dropout Voltage vs. Output Current, 3.6 V Version

TYPICAL CHARACTERISTICS



Figure 15. Quiescent Current vs. Input Voltage, 0.7 V Version



Figure 16. Quiescent Current vs. Input Voltage, 2.5 V Version



Figure 17. Quiescent Current vs. Input Voltage, 3.6 V Version



Figure 18. PSRR vs. Frequency, 0.7 V Version



Figure 19. PSRR vs. Frequency, 2.5 V Version



Figure 20. PSRR vs. Frequency, 3.6 V Version

TYPICAL CHARACTERISTICS



Figure 21. Output Noise vs. Frequency, 0.7 V Version



Figure 22. Output Noise vs. Frequency, 2.5 V Version



Figure 23. Output Noise vs. Frequency, 3.6 V Version



Figure 24. Line Transients, 0.7 V Version

TYPICAL CHARACTERISTICS



Figure 25. Line Transients, 2.5 V Version



Figure 26. Line Transients, 3.6 V Version



Figure 27. Load Transients, 0.7 V Version, Load Step 1 mA to 400 mA

TYPICAL CHARACTERISTICS



Figure 28. Load Transients, 2.5 V Version, Load Step 1 mA to 400 mA



Figure 29. Load Transients, 3.6 V Version, Load Step 1 mA to 400 mA



Figure 30. Load Transients, 0.7 V Version, Load Step 50 mA to 100 mA

TYPICAL CHARACTERISTICS



Figure 31. Load Transients, 2.5 V Version, Load Step 50 mA to 100 mA



Figure 32. Load Transients, 3.6 V Version, Load Step 50 mA to 100 mA



Figure 33. Turn On with CE Behavior, 0.7 V Version

TYPICAL CHARACTERISTICS



Figure 34. Turn On with CE Behavior, 2.5 V Version



Figure 35. Turn On with CE Behavior, 3.6 V Version



Figure 36. Turn Off with CE Behavior, 0.7 V Version

TYPICAL CHARACTERISTICS



Figure 37. Turn Off with CE Behavior, 2.5 V Version



Figure 38. Turn Off with CE Behavior, 3.6 V Version

APPLICATION INFORMATION

A typical application circuit for NCP4687 series is shown in the Figure 39.



Figure 39. Typical Application Schematic

Input Decoupling Capacitor (C1)

A 1.0 μF ceramic input decoupling capacitor should be connected as close as possible to the input and ground pin of the NCP4687 device. Higher values and lower ESR improves line transient response.

Output Decoupling Capacitor (C2)

A 1.0 μF ceramic output decoupling capacitor is sufficient to achieve stable operation of the device. If tantalum capacitor is used, and its ESR is high, the loop oscillation may result. The capacitor should be connected as close as possible to the output and ground pin. Larger values and lower ESR improves dynamic parameters.

Enable Operation

The enable pin CE may be used for turning the regulator on and off. The IC is switched on when a high level voltage is applied to the CE pin. The enable pin has an internal pull down current source which assure off state of LDO in case the CE pin will stay floating. If the enable function is not needed connect CE pin to V_{IN}.

The D version of the NCP4687 device includes a transistor between V_{OUT} and GND that is used for faster discharging of the output capacitor. This function is activated when the IC goes into disable mode.

Thermal Consideration

As a power across the IC increase, it might become necessary to provide some thermal relief. The maximum power dissipation supported by the device is dependent upon board design and layout. Mounting pad configuration on the PCB, the board material, and also the ambient temperature affect the rate of temperature increase for the part. When the device has good thermal conductivity through the PCB the junction temperature will be relatively low in high power dissipation applications.

The IC includes internal thermal shutdown circuit that stops operation of regulator, if junction temperature is higher than 165°C. After that, when junction temperature decreases below 100°C, the operation of voltage regulator would restart. While high power dissipation condition is, the regulator starts and stops repeatedly and protects itself against overheating.

Sense Pin

The SENSE pin improves significantly the load regulation. The connection resistance between the LDO and the load given by PCB parameters has reduced impact to load regulation. If possible, use wide PCB traces as short as possible.

ORDERING INFORMATION

Device	Marking	Nominal Output Voltage	Feature	Package	Shipping†
NCP4687DH12T1G	A12D	1.2 V	Auto discharge	SOT−89 (Pb−Free)	1000 / Tape & Reel
NCP4687DH15T1G	A15D	1.5 V	Auto discharge	SOT−89 (Pb−Free)	1000 / Tape & Reel
NCP4687DH18T1G	A18D	1.8 V	Auto discharge	SOT−89 (Pb−Free)	1000 / Tape & Reel
NCP4687DH25T1G	A25D	2.5 V	Auto discharge	SOT−89 (Pb−Free)	1000 / Tape & Reel
NCP4687DH33T1G	A33D	3.3 V	Auto discharge	SOT−89 (Pb−Free)	1000 / Tape & Reel
NCP4687DMX18TCG	9P	1.8 V	Auto discharge	XDFN6 (Pb−Free)	5000 / Tape & Reel
NCP4687DMX25TCG	9X	2.5 V	Auto discharge	XDFN6 (Pb−Free)	5000 / Tape & Reel
NCP4687DMX33TCG	0G	3.3 V	Auto discharge	XDFN6 (Pb−Free)	5000 / Tape & Reel
NCP4687DSN18T1G	J18	1.8 V	Auto discharge	SOT−23 (Pb−Free)	3000 / Tape & Reel
NCP4687DSN25T1G	J25	2.5 V	Auto discharge	SOT−23 (Pb−Free)	3000 / Tape & Reel
NCP4687DSN28T1G	J28	2.8 V	Auto discharge	SOT−23 (Pb−Free)	3000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

SCALE 2:1

SOT−23 5−LEAD
CASE 1212−01
ISSUE A

DATE 28 JAN 2011





NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSIONS: MILLIMETERS.
3. DATUM C IS THE SEATING PLANE.

	MILLIMETERS	
DIM	MIN	MAX
A	---	1.45
A1	0.00	0.10
A2	1.00	1.30
b	0.30	0.50
c	0.10	0.25
D	2.70	3.10
E	2.50	3.10
E1	1.50	1.80
e	0.95 BSC	
L	0.20	---
L1	0.45	0.75

RECOMMENDED SOLDERING FOOTPRINT*



DIMENSIONS: MILLIMETERS

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



XXX = Specific Device Code
M = Date Code
▪ = Pb−Free Package
(Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “ ▪”, may or may not be present.

DOCUMENT NUMBER:	98ASH70518A	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	SOT−23 5−LEAD	PAGE 1 OF 1

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

SOT−89, 5 LEAD
CASE 528AB−01
ISSUE O

DATE 23 NOV 2009



SCALE 2:1



TOP VIEW



SIDE VIEW



BOTTOM VIEW

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. LEAD THICKNESS INCLUDES LEAD FINISH.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.
5. DIMENSIONS L, L2, L3, L4, L5, AND H ARE MEASURED AT DATUM PLANE C.

	MILLIMETERS	
DIM	MIN	MAX
A	1.40	1.60
b	0.32	0.52
b1	0.37	0.57
c	0.30	0.50
D	4.40	4.60
D2	1.40	1.80
E	2.40	2.60
e	1.40	1.60
H	4.25	4.45
L	1.10	1.50
L2	0.80	1.20
L3	0.95	1.35
L4	0.65	1.05
L5	0.20	0.60

GENERIC MARKING DIAGRAM*



XXXX = Specific Device Code
MM = Lot Number
▪ = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G”, may or not be present.

RECOMMENDED MOUNTING FOOTPRINT*



DIMENSIONS: MILLIMETERS

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

DOCUMENT NUMBER:	**98AON47037E**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**SOT−89, 5 LEAD**	**PAGE 1 OF 1**

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

XDFN6 1.20x1.20, 0.40P
CASE 711AH
ISSUE O

SCALE 4:1

DATE 14 SEP 2011



NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.25mm FROM TERMINAL TIPS.
4. COPLANARITY APPLIES TO ALL OF THE TERMINALS.

	MILLIMETERS	
DIM	MIN	MAX
A	---	0.40
A1	0.00	0.05
b	0.13	0.23
D	1.20 BSC	
D2	0.89	0.99
E	1.20 BSC	
E2	0.25	0.35
e	0.40 BSC	
L	0.15	0.25
L1	0.05 BSC	

GENERIC MARKING DIAGRAM*



XX = Specific Device Code
MM = Date Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “ ▪”, may or may not be present.

RECOMMENDED MOUNTING FOOTPRINT*



DIMENSIONS: MILLIMETERS

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

DOCUMENT NUMBER:	98AON59261E	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	XDFN6, 1.20 X 1.20, 0.40P	PAGE 1 OF 1

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Email Requests to: orderlit@onsemi.com

onsemi Website: www.onsemi.com

TECHNICAL SUPPORT
North American Technical Support:
Voice Mail: 1 800−282−9855 Toll Free USA/Canada
Phone: 011 421 33 790 2910

Europe, Middle East and Africa Technical Support:
Phone: 00421 33 790 2910
For additional information, please contact your local Sales Representative

◊