






联系方式 18058866958

**SPECIFICATIONS**

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25℃~+85℃
- 4、Contact Resistance: 30mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 800V AC/minute
- 7、Material:Housing PA66, UL94V-0



编 号	尺寸 (mm)	
	A	B
HC-XHD-2*2Y	2.50	7.50
HC-XHD-2*3Y	5.00	10.00
HC-XHD-2*4Y	7.50	12.50
HC-XHD-2*5Y	10.00	15.00
HC-XHD-2*6Y	12.50	17.50
HC-XHD-2*7Y	15.00	20.00
HC-XHD-2*8Y	17.50	22.50
HC-XHD-2*9Y	20.00	25.00
HC-XHD-2*10Y	22.50	27.50
HC-XHD-2*11Y	25.00	30.00
HC-XHD-2*12Y	27.50	32.50

GENERL TOLERANCE	制 图 DRAWING	钱岳生 2016、09、22	料 号 PART NO.	HC-XHD-2*NY	版 本 REV.	A
X.X±0.25 X:±2'	审 核 CHECK	张 名 2016、09、23	品 名 TITLE	XHD2.5弯针 WAFER DIP TYPE	页 次 SHEET	1/1
X.XX±0.20	核 准 APPROVAL	张 名 2016、09、24	客 户 料 号 CUTM. NO.			
X.XXX±0.10	单 位 UNITS	MM	比 例 SCALE	1:1		
深圳市华灿天禄电子有限公司						