



MATERIAL:
 Housing : PBT UL94V-0 Beige
 Contacts: Brass
 Lock: Phosphor Bronze

ELECTRICAL CHARACTERISTICS:
 Current Rating: 2 AMP
 Dielectric Withstanding Voltage: AC1000V for 1minute
 Insulator Resistance: 1000MΩ min at DC 500V
 Contact Resistance: 20mΩ max at DC 100mA
 Operating Temperature: -55°C ~ +125°C

Pitch	Position	Rows with Contacts	Contact Arrange
2.54mm	96	a b c	
	64	a - c	
	32	a - -	

MODEL: 9001-11x1CxXA	DRAWN BY : Leiqin	DATE:
TITLE : 2.54弯公胶芯+弯针欧式连接器	CHECKED BY : Liwei	DATE:
DRAWING NO:	REV. : A	APPROVED BY: Wuxin
SHEET: 1 OF 1	SCALE: 3:1	SIZE: A4 UNIT : mm

GENERAL TOLERANCE:
 (UNLESS SPECIFIED)
 X. ±0.30mm X.* ± 3*
 X.X ±0.25mm X.X' ± 2*
 X.XX ±0.20mm X.XX' ± 1*
 X.XXX±0.10mm X.XXX ± 0.5*

MEASURE POINT:
 QUADRANT POINT
 TANGENCY POINT
 INTERSECTION POINT

NO:	PARTICULAR	BY	DATE
REVISIONS			

深圳市吉威电子有限公司
 SZJUSTWELL ELECTRONICS CO., LTD