



安远县鑫富晶电子科技有限公司

承 认 书 APPROVED SHEET

品名 (Description) : 铝电解电容器 ELECTROLYTIC CAPACITORS

系列规格 (Series) : S7 1Uf/50V 4*7 XSH105M050T4A5B07A 编带脚
距 2.5mm

客户:

深圳市华秋电子有限公司

承认栏

APPROVED COLUMN

发行栏

APPROVED COLUMN

(确认后敬请惠返一份)

地址: 江西省赣州市安远县产城新区 3 号地块 2.3.4 栋

电话: 0797-3793369

传真: 0797-3793369

制表: 连晶晶

审核: 邹建明



铝电解电容器样品规格表（主要参数）

序号	系列	规格		尺寸 (mm)	脚距 F (mm)	容量 偏差 (%)	允许 最大 损耗角 DF(%)	允许最大 纹波电流 (mA rms/ 120HZ 105°C)	允许 最大 漏电流 LC(μ A)	阻抗 ESR (Ω)	成型 方式
		容量 (uF)	电压 (V)								
1	S7	1	50	4*7	1.5	±20	10	10	50		编带 2.5mm
2											
3											
4											
5											

注：1、电容量、损耗角测量条件为温度 $20\pm 2^{\circ}\text{C}$ ，频率 $120\pm 12\text{HZ}$ ，电压 $0.5\text{Vrms} + 1.5\sim 2.0\text{V.DC}$ 。


2、漏电流测量条件为温度 $20\pm 2^{\circ}\text{C}$ ，串联 $1\text{k}\Omega \pm 10\Omega$ 的保护电阻，升到UR后2 分钟时读数，取较大者。

3、等效串联电阻（ESR）测量条件为温度 $20\pm 2^{\circ}\text{C}$ ，频率 100KHZ ，电平 1.0V ,测试夹具须靠近引线根部。

4、所有数据以承认书和实际的样品测试参数为准。

电容器的构成分解图示：

正箔、负箔、电解纸、正负导针、电气胶带(胶水)、电解液、胶粒 、铝壳、胶管。



序号	材料名称	功用
1	正、负极铝箔	存储电荷
2	正、负极导针	引出线
3	电解纸	绝缘(隔离), 并吸附电解液
4	电气胶带(胶水)	缠附芯子, 使之不松散
5	电解液	电容器的真正负极; 也有修复铝箔氧化膜的作用
6	胶粒	绝缘、密封、固定芯子
7	铝壳	隔离保护、密封
8	胶管(套管)	标示、绝缘

产品系列 (SERIES) S7 105°C

1. 执行标准 (Applicable Standard) : JISC 5141
2. 工作电压及温度范围 (Operating Temperature Range) :
6.3V ~ 100 V, -40 °C ~ +105°C
3. 标称容量范围 (Nomai Capacitance Rage)
0.1μF~15000μF

4. 额定电压和突破电压:

额定电压 Rated Voltage (V)	6.3	10	16	25	35	50	63	100	250
突破电压 Surge Voltage (V)	8	13	20	32	44	66	84	132	300

5. 漏电流 (DC Leakage Current)

电容施加额定工作电压, 2 分钟后, 其漏电流 $I \cong 0.01 CV$ or $3 \mu A$ (取最大值)
 Applying the rated DC voltage to the capacitor. The leakage current is measured at 2 minutes after the DC voltage across the capacitor reached the rated voltage. The leakage current shall not exceed the value below. (at 25°C)
 $I \cong 0.01 CV$ or $3 \mu A$, whichever is greater

I : Leakage current (μA) C : Nominal capacitance (μF) V : Rated voltage (V)

6. 容量偏差 (Capacitance Tolerance) :

容量允许偏差: -20 ~ +20% (at 20°C, 120Hz)
 The capacitance shall be within the following tolerance to the nominal capacitance. -20 ~ +20% (at 20°C, 120Hz)

7. 损失角 (Tangent of Loss Angle (Tanδ):

损失角满足下表要求, 对于容量大于 1000μF 的产品, 每超过 1000μF, 损失角增加 0.02。
 Tan δ shall not exceed the value below. (at 20°C, 120Hz), When nominal capacitance is over 1000μF. Tanδ shall be added 0.02 to the listed, value with increase of every 1000μF.

额定电压 Rated Voltage (V)	4	6.3	10	16	25	35	50	63	100	250
损失角 Tan δ	0.20	0.22	0.19	0.16	0.14	0.12	0.20	0.09	0.08	0.24

8. 温度特性 (Temperature Characteristics)

电容器的阻抗特性满足下表要求。
 Impedance ratio of the -25°C or -40°C value to the 25°C value shall not exceed the value below. (at 120Hz)

Rated Voltage (V)	4	6.3	10	16	25	35	50	63	100
Z (-25°C) / Z (20°C)	6	4	3	2					
Z (-40°C) / Z (20°C)	12	10	6	4	3				

9. 寿命试验 (Load Life)

电容器施加额定工作电压，105℃ 2000 小时后，冷却至 20℃，测试其特性满足下表要求。

The following specifications shall be satisfied when the capacitors are restored to 20℃, after the rated voltage is applied for 2000 hours at 105℃.

容量变化 (Capacitance change)	≅ ±20% of the initial value
损失角 (Tan δ)	≅ 200% of the initial specified value
漏电流 (Leakage current)	≅ the initial specified value
Mechanical	No leakage and undamaged

10. 高温储存试验 (Shelf Life)

电容器不加电压，放置在 105℃，1000 小时后，冷却至 20℃，测试其特性满足下表要求。

The following specifications shall be satisfied when the capacitors are restored to 20℃, The capacitors shall be subjected to voltage treatment specified in item 4.4 of JIS C 5102, before the measurements.

容量变化 (Capacitance change)	≅ ±20% of the initial value
损失角 (Tan δ)	≅ 200% of the initial specified value
漏电流 (Leakage current)	≅ the initial specified value
Mechanical	No leakage and undamaged


11. 标志 (Marking)

电容器外表标志如下项目 (套管表面)


The following items shall be marked on each capacitor. (Note : White marking on black sleeve)

Example(直径大于 8 mm 的产品有防爆阀 Safety vent more than 8 mm Dia product)

- 1) 最高工作温度 Maximum operating temperature
- 2) 安全装置 Safety device
- 3) 极性 Polarity
- 4) 标称容量 Nominal capacitance
- 5) 标称电压 Rated voltage
- 6) 商标 Manufacturer's identification mark



12. 外形图 Dimensions (mm)



13. 引线间距和引线直径(Lead Spacing and Wire Diameter)

ΦD	4	5	6	8	10	12	13	16	18	22
F	1.5	2.0	2.5	3.5	5.0		7.5		10	
Φd	0.5	0.5	0.5	0.5	0.6		0.8	0.8	1.0	
α	1.0				1.5				2.0	

14. 纹波电流 (Ripple Current Coefficients)

频率因子 Frequency Multipliers

Freq.(Hz)		120	1K	10K	100K
Cap.(μ F)	0.1 ~ 180	0.4	0.75	0.9	1.0
	220 ~ 560	0.5	0.85	0.94	1.0
	1000 ~ 15000	0.85	0.95	0.98	1.0

温度因子 (Temperature Multipliers)

Temp.(°C)		≦ 75	85
WV	6.3 ~ 100	1.40	1.00

客户料号	XSH105M050T4A5B07A	规格	1uF/ 50V	尺寸	4*7	
出货商标	Xfjcap	出货数	10 PCS	抽样数	10PCS	
抽样计划	MIL-STD-105E II 级水准 严重缺陷: AQL=0%, 主要缺陷: AQL=0.15%, 轻微缺陷: AQL=0.65%					
测试条件	测试频率: <u>120 HZ</u> 漏电流测试电压: <u>50</u> V 测试时间: <u>1</u> 分钟 100KHZ 测试阻抗 ESR					
	温度: 26°C		湿度: 62%			
NO.	容量 CAP(uF)	损失角 DF(%)	漏电流 LC(uA)	阻抗 ESR(Ω)	脚距 (MM)	备注
标准值	$\pm 20\%$	≤ 10	≤ 3	\leq	1.5	成型脚距 2.5mm
1	1.01	2.2	0.15			
2	1.02	2.1	0.13			
3	1.03	2.0	0.12			
4	0.99	1.9	0.11			
5	0.98	1.8	0.12			
6	0.99	1.9	0.13			
7	1.01	2.1	0.14			
8	1.00	2.0	0.12			
9	1.03	2.2	0.11			
10	1.02	2.1	0.12			
环保测试	依据 RoHS 质量要求: 均质材料: Pb \leq 200ppm,Cd \leq 40ppm,Hb \leq 200ppm,Cr \leq 200ppm,PBB \leq 200ppm,,PBDE \leq 200ppm,包装材料: Pb+ Cd+Hg+Cr+(VI) \leq 60ppm; 电镀材质: 电镀层不得含有六价 Cr+.					
环保性能	不含有 CMDC43 中规定的 I 级环境管理物质。					
检验结论	OK			审核	检验员	检验日期
				邹建明	连晶晶	2023-05-15