



P.C.B LAYOUT

MATERIAL:
 Housing : PBT UL94V-0 Beige
 Contacts: Brass
 Lock: Phosphor Bronze

ELECTRICAL CHARACTERISTICS:
 Current Rating: 2 AMP
 Dielectric Withstanding Voltage: AC1000V for 1minute
 Insulator Resistance: 1000MΩ min at DC 500V
 Contact Resistance: 20mΩ max at DC 100mA
 Operating Temperature: -55°C ~ +125°C

Pitch	Position	Rows with Contacts	Contact Arrange
2.54mm	96	a b c	
	64	a - c	
	32	a - -	

MODEL: 9001-1 3xx0CxxA	DRAWN BY : Leiqin	DATE:
TITLE : 2.54弯公胶芯+直针欧式连接器	CHECKED BY : Liwei	DATE:
DRAWING NO:	REV. : A	APPROVED BY: Wuxin
SHEET: 1 OF 1	SCALE: 3:1	SIZE: A4
	UNIT : mm	

GENERAL TOLERANCE:
 (UNLESS SPECIFIED)

X.	±0.30mm	X.*	±	3*
X.X	±0.25mm	X.X*	±	2*
X.XX	±0.20mm	X.XX*	±	1*
X.XXX	±0.10mm	X.XXX*	±	0.5*

MEASURE POINT:
 QUADRANT POINT
 TANGENCY POINT
 INTERSECTION POINT

NO:	PARTICULAR	BY	DATE
REVISIONS			

深圳市吉威电子有限公司
 SZJUSTWELL ELECTRONICS CO., LTD