



*P.C.B LAYOUT*

SPECIFICATIONS

- Rated Current : 3.0AMP
- Contact Resistance : 20mΩ Max
- Withstand Voltage : 500V AC/DC
- Insulation Resistance : 1000MΩ Min
- Operation Temperature : -40°C to +108°C
- Contact Material : Brass
- Contact Plating : Au or Sn Over Ni
- Insulator Material : Polyester(UL94V-0)
- Standard : PA6T
- Max Processing Temp : 230°C for 5-10 seconds

MODEL: 2.54-2x nP L35-H2.5	DRAWN BY : Leiqin	DATE:	GENERAL TOLERANCE: (UNLESS SPECIFIED)
TITLE : 双层双排塑高2.5直插排针	CHECKED BY : Liwei	DATE:	X. ±0.30mm X. ±
DRAWING NO:	REV. : A	DATE:	X.X ±0.25mm X.X ±
SHEET: 1 OF 1	SCALE: 3:1	DATE:	X.XX ±0.20mm X.XX ±
	SIZE: A4	DATE:	X.XXX±0.10mm X.XXX ±
	UNIT : mm	DATE:	



**深圳市吉威电子有限公司**  
SZJUSTWELL ELECTRONICS CO., LTD

NO:	BY	DATE
REVISIONS		

A B C D E F

1 2 3 4 5 6 7 8 9

MEASURE POINT:  
QUADRANT POINT  
TANGENCY POINT  
INTERSECTION POINT

GD  
FD  
TD  
PD

http://www.szjustwell.com 0755-33000755