



Recommended P.C.B Layout(Top Side)  
(PCB BOARD TOLERANCE±0.05)

**SPECIFICATIONS**  
 Rated Current:3.0AMP  
 Contact Resistance:20mΩ Max  
 Withstand Voltage:1000V AC/DC  
 Insulation Resistance:1000MΩ Min  
 Operation Temperature:-40°c to +105°c

Contact Material:Brass  
 Contact Plating:Au or Sn Over Ni  
 Insulator Material:Polyester(UL94V-0)  
 Standard: PBT  
 Max.Processing Temp: 180°C for 30-60 seconds  
 (200°C for 10 seconds)

MODEL: BH-2.54HDR-2X nP	DRAWN BY : Leiqin	DATE:	GENERAL TOLERANCE: (UNLESS SPECIFIED)
TITLE : 2.54筒半90°	CHECKED BY : Liwei	DATE:	X. ±0.30mm X.' ± 3'
DRAWING NO:	REV. : A	DATE:	X.X ±0.25mm X.X' ± 2'
SHEET: 1 OF 1	SCALE:3:1	DATE:	X.XX ±0.20mm X.XX' ± 1'
	SIZE: A4	DATE:	X.XXX±0.10mm X.XXX' ± 0.5'
	UNIT : mm	DATE:	



**深圳市吉威电子有限公司**  
**深圳市元吉威电子有限公司**

MEASURE POINT:  
 QUADRANT POINT (QP)  
 TANGENCY POINT (TP)  
 INTERSECTION POINT (IP)

NO:	PARTICULAR	BY	DATE
REVISIONS			
1			
2			
3			
4			
5			
6			
7			
8			