



SPECIFICATIONS

Current rating: 2A AC/DC
 Voltage rating: 250V AC/DC
 Contact resistance: 20mΩ max.
 Withstand voltage: 1000V AC/min
 Insulation resistance: 1000MΩ/min.
 Temperature range: -25°C~+85°C
 Applicable PC board thickness: 0.063"(1.6)

Material:

Part No: 2~16
 HOUSING: PA66, UL 94V-0/2

Poles	DI mensi ons mm		
	A	B	C
2	2.00	5.6	3.2
3	4.00	7.6	4.0
4	6.00	9.6	5.0
5	8.00	11.6	6.2
6	10.00	13.6	8.2
7	12.00	15.6	10.2
8	14.00	17.6	12.2
9	16.00	19.6	14.2
10	18.00	21.6	16.2
11	20.00	23.6	14.2
12	22.00	25.6	16.2
13	24.00	27.6	16.2
14	26.00	29.6	16.2
15	28.00	31.6	16.2
16	30.00	33.6	16.2

TOLERANCE TABLE	
.0	±0.20
.00	±0.10
.000	±0.05

APPROVED:	DATE:	TITLE: 深圳市灿科盟实业有限公司 CHANKLEMENT INDUSTRYCO., LTD			
CHECKED:	DATE:	CLIENT P/N /			
DRAWN:	DATE:	UNIT	SCALE	REV.	A
hh-H	2019-05-17	mm	Free	1	1B50